

Product Range

Functional Explanation



ONE-TOUCH FITTING

- Push to connect fitting
- Commonly used for a whole range of pneumatic applications
- No tools needed
- Fast Installation & Quick Disconnection

ONE-TOUCH FITTINGS



COMPACT ONE-TOUCH FITTING

- Lightweight & Compact fitting
- Electroless nickel (ENI) plating type
- Suitable for small equipment & narrow space
- Fast installation & Quick Disconnection

COMPACT ONE-TOUCH FITTINGS





SPEED CONTROLLERS

- Precise control of airflow rate
- Designed to secure a large airflow and to control high air speed
- Lightweight & Quick installation
- Increased the number of needle rotational 10-12!
- NISO Di type: easy adjustment by using tools in a narrow space

PILOT CHECK VALVES SPEED CONTROLLERS

- Combination of pilot check valves and speed controllers
- Able to adjust airflow speed
- Enables 360° direction for tube mounting



HAND VALVES, HAND SLIDE VALVES

- Used for turning air pressure on/off
- The three-ways control, when closed, discharged the residual pressure from the output side. Thus, assures safety at adjustment or repairment

STOP FITTINGS

- One touch fitting with built-in stop valve
- Used for frequent change of pneumatic connections
- The flow-shut mechanism operates to stop the air flow when the tube is disconnected
- Allows air flow when the tube is connected





CHECK VALVES

- Permits the air flow in one direction but block the flow in the opposite direction
- Keeps the output pressure at a constant level
- Suitable for low air pressure

STAINLESS STEEL (SUS316L)

- Lock-claws push-in fitting made of SUS316
- Used in all sectors related to food, medical, and precision parts
- Rotating body structure
- Fast installation & Quick disconnection
- Suitable for high temperature and Excellent corrosion resistance



BRASS PUSH-IN FITTINGS

BRASS PUSH-IN FITTINGS

- One-touch fitting made of brass/body & release ring
- Compact type & suitable for narrow space
- Excellent flame/spitter resistance and heat resistance






TWO-TOUCH FITTINGS

- Nut-tightened air connector for pneumatic piping
- Used in places with severe shock and vibration
- Excellent chemical resistance and corrosion resistance
- Semi-permanent

SILENCER

- Connected to the exhaust port of a device, suppresses that exhaust noise
- Provides superior performance in noise control and a minimum effect on air efficiency
- Compact and lightweight
- Suitable for air and gas
- Plastic and metal silencers available



OIL EJECTOR LINE

- Excellent for cutting oil supply and washing process
- Excellent chemical resistance, corrosion resistance and nonconductive
- Lightweight and semi-permanent made of plastic
- Comes with various sizes

OIL EJECTOR LINES





TUBE(PU, PE, NA, COIL)

- Offer excellent flexibility and outstanding use in a wide range of applications
- Used for pneumatic applications, food industry
- Featuring excellent flexibility, oil-resistance, wear-resistance and cold-resistance
- Wide range of color options

AIR GUN

- Efficient blowing of air, ideal the cleaning of parts and surfaces
- Adjustable air injection volume
- Used in limited spaces due to various nozzle length



COUPLING

- Used to connect pneumatic device
- One-way switch valve built-in automatic on-off valve
- Easy to use due to connection and release of plug and socket being smooth
- Wide range of coupling available

KOREAN COUPLING

- Used to connect pneumatic device
- One-way switch valve built-in automatic on-off valve
- Easy to use due to connection and release of plug and socket being smooth
- Wide range of coupling available





TWO-TOUCH FITTINGS (BSBM)

- Screw joining fitting for severe shock and vibration
- Attached insert allows tolerance top pressure and vibration
- Efficient connection because of thread part coating

TWO-TOUCH FITTINGS (BSBM)



BARB FITTINGS



BARB FITTINGS

- Miniature fitting
- Easy to use, simple to assemble, and high cost-efficient
- Clean design





Caution and Warning

DANGER death or serious injury may occur

WARNING death or serious injury may occur depending on the specific situation

CAUTION serious/light injury or loss of property may occur depending on the specific situation

DANGER

Do not use CDCPNEUMATIC products under the following conditions

- Devices used for maintaining and handling human life and body
- Devices for moving and transporting human
- Devices that prioritize safety purposes

WARNING

Do not use CDCPNEUMATIC products under the following conditions

- Beyond the specifications stated in the catalog or the instructions
- Excessive vibrations, impacts
- Avoid any load on products such as tensile strength, twisting and bending
- Exposure spatter (there is a risk of causing fire by sparks)
- Under condition of over 60 °C, hot temperature fluid (hydrolysis may occur) or thermal oil
- Exposure/adhere to corrosive gas, inflammable gas, chemicals, seawater, water and vapor (except some products)
- For Use in water (damaged by surge pressure)
- Under condition of pharmaceuticals being used (see chemical compatibility table)

CAUTION

Pay attention to the following

- Remove dusts or drain before installation
- Supply air after connection fitting to the pipe. There is a possibility that the seal of fitting may come off and cause leakage.
- Excessive force and exceeding the recommended allowable torque may cause damage or quality problems due to broken screws.
- Tube detachable sleeve is designed in a circular shape, thus, suitable for the narrow space. However, in case of space being limited select other products (compact fitting and etc.)

Common Safety Instructions

- 〈Table〉 Recommended Tightening Torque(Thread Size)

Thread type	Thread Size	Recommended torque(kg·cm)
Metric Thread (mm)	M3 × P0.5	0.7 Nm
	M5 × P0.8	1.5 Nm
	M6 × P1.0	2.3 Nm
	R 1/8	2 Nm
Pipe Taper Thread (PT)	R 1/8	12 Nm
	R 1/4	22 Nm
	R 3/8	28 Nm
	R 1/2	1.5 Nm
Unified Thread (UNF)	No. 10-32 UNF	7 Nm
	NPT 1/8	7 Nm
	NPT 1/4	12 Nm
	NPT 3/8	22 Nm
NPT Thread	NPT 1/2	28 Nm
	G 1/8	10 Nm
	G 1/4	15 Nm
	G 3/8	25 Nm
PF Thread	G 1/2	40 Nm
	G 5/8	40 Nm


- Please check tube mounting length before connecting a fitting into a tube.
- When inserting a tube, the tube needs to be inserted fully into the pushing in fitting to the end. It goes through the packing till the endpoint BL.
- When the tube is completely installed, lock-claws tightens and it is sealed by packing.

(Lines/mm)

Metric Size O.D. Tolerance							Unit/Inch
Tube Size	Ø3	Ø4	Ø6	Ø8	Ø10	Ø12	Ø12
Tolerance	±0.1	±0.1	±0.1	±0.1	±0.15	±0.15	±0.15

Inch Size O.D. Tolerance							Unit/Inch
Tube Size	Ø1/4	Ø1/2	Ø3/8	Ø1/2	Ø1/2	Ø3/4	Ø1/2
Tolerance	±0.1	±0.01	±0.1	±0.1	±0.15	±0.15	±0.15

- Check the tolerance of the outer diameter of the tube before use CDCPneumatic products
- The tolerance for the outer diameter of the tube that can be mounted on the product is $\pm 0.1\text{mm}$ to $\pm 0.15\text{mm}$ from the standard diameter. Please refer to the table for the tolerance for each size.



<Table> Standard Fitting Type

Tube Mounting Depth	Standard Type						Compact Type		
	ø4	ø6	ø8	ø10	ø12	ø16	ø3	ø4	ø6
B	15.0	16.5	18.8	20.1	22.9	23.6	11.3	11.8	12.9

Standard Type

Tube Mounting Depth	Standard Type						Compact Type		
	ø1/2	ø3/8	ø1/4	ø3/16	ø3/8	ø1/2	ø1/4	ø3/8	ø1/4
B	15.0	15.9	16.8	18.8	20.1	23.1	11.3	11.8	13.5

- Please check screw dimensions and thread size before use
- The taper pipe thread is coated with Teflon, thus requiring no additional Teflon tape or sealing treatment



〈Table〉 Metric Thread Size

Thread type	M Thread		R Thread				U Thread	NPT Thread			
Thread Size(T)	M5	M6	R1/8	R1/4	R3/8	R1/2	UNF 1/8	R1/8	R1/4	R3/8	R1/2
Thread Length(A)	4	4.1	8	10	11	14	4.1	8.5	10.5	11.5	14.5

Thread Code	Thread Size	Applicable product
M3	M3 x 0.5	(Applied to all products)
M5	M5 x 0.8	
M6	M6 x 1.0	

• Tube Insertion

- Make sure that the tube inserts fully into the fitting.
- Make sure that the cut end surface of the tube is a right angle without a scratch on the surface and deformations. Pull the tube lightly to check the complete installation.
- There is a risk of leakage when there is damage to the outside of the tube
- Check tube diameter to avoid tube damage.

- Make sure there is no air pressure inside of the tube before disconnection it
- Push the release ring of the push-in fitting evenly and deeply enough to pull out the tube by hand
- Cut the compressed part of the tube before reuse

1 Preparation	prepare the tube, tube cutter, fitting connection devices(spanner or monkey wrench)
2 Tube cutting	cut the tube at a right angle axial and vertically using tube cutter
3 Fitting installation	Tighten the fitting with the spanner or monkey referring recommended Tightening Torque
4 Tube insertion	insert the tube in a straight line into the fitting after marking the length of the tube insertion

- When removing a fitting, use proper tools to loosen
- Remove the sealant stuck on the mating equipment
- Please refer to the size of sleeve



〈Image〉 X, Y size

<Table> The Size of Sleeve

► The Size of Standard Sieve Type										Unit/mm
Sieve specification	Standard Type						Compact Type			
	φ4	φ6	φ8	φ10	φ12	φ14	φ16	φ3	φ4	φ6
X	9.7	11.8	13.8	16.6	19.8	22	25.2	7.2	8.2	10.2
Y	-	-	-	-	-	-	-	9.2	10.4	12.4

► The Size of Inch Sleeve Type

Sieve specification	Standard Type						Compact Type		
	Ø1/2	Ø1/4	Ø1/4	Ø1/8	Ø3/8	Ø1/2	Ø1/4	Ø1/8	Ø1/4
X	9.7	11.1	12.6	13.8	16.8	19.9	7.2	8.2	10.8
Y	-	-	-	-	-	-	9.2	10.4	12.8

ONE-TOUCH FITTINGS



Product Code System

METRIC - BSP(F)

PC 06-01-N

ONE TOUCH FITTING	TUBE DIA CODE SIZE	THREAD SIZE CODE SIZE	PLATING None
04	04	M6	M6×0.8
06	06	M8	M8×1.0
08	08	M10	M10×1.5
10	10	M12	M12×1.5
12	12	M14	M14×1.5
14	14	M16	M16×1.5
16	16	M18	M18×1.5

METRIC - BSP(F)

PC 06-G01

ONE TOUCH FITTING	TUBE DIA CODE SIZE	THREAD SIZE CODE SIZE
04	04	G1/8"
06	06	G1/4"
08	08	G3/8"
10	10	G1/2"
12	12	G3/4"
14	14	G1"
16	16	G1 1/8"

INCH - BSP(F)

PC-1/4-01

ONE TOUCH FITTING	TUBE DIA CODE SIZE	THREAD SIZE CODE SIZE
1/8"	1/8"	R1/8"
1/4"	1/4"	R1/4"
3/8"	3/8"	R3/8"
1/2"	1/2"	R1/2"
5/8"	5/8"	R5/8"
3/4"	3/4"	R3/4"

INCH - NPT

PC-1/4-N1

ONE TOUCH FITTING	TUBE DIA CODE SIZE	THREAD SIZE CODE SIZE
1/8"	1/8"	NPT 1/8"
1/4"	1/4"	NPT 1/4"
3/8"	3/8"	NPT 3/8"
1/2"	1/2"	NPT 1/2"
5/8"	5/8"	NPT 5/8"
3/4"	3/4"	NPT 3/4"

Uses

- One-touch joints used in pneumatic piping
- Used for various environments to meet all needs


Features

- Easy installation and disconnection by one touch
- PC type is effective for piping in narrow spaces as the inner and outer sides are hexagonal
- PL and PT types have a rotating structure, thus, efficient for piping
- It is easily disconnected by pushing the tube without tools

Specifications

Fluid type	Air/No other gases or liquids
Working pressure	0~150PSI / 0~9.9kgf/cm ² (0~990kPa) ※In combination with the applied tube, it is based on the maximum operating pressure of the tube.
Negative pressure	-29.5 in Hg / -750mmHg(-750Torr)
Working temperature	32~140° F / 0~60°C
Applicable Tube	Polyurethane and Nylon

Structural drawing



Example of uses

- Use a hexagonal wrench or spanner to tighten internal and external hexagonal part
- PL and PT type are flexible for directional tube laying given its revolving connection of body
- Sleeve is circular, thus, no interference with equipment



CAUTIONS

- Be sure to read "Caution", "Warning", "Common Safety Instructions"(pp. 25) and precautions of using fitting products before use.
- Make sure to check "Recommended Tightening Torque"(pp.26)
- It is recommended to rotate the fitting 2-3 times using a tool after tightening by hand. Screws will break if it pushes too hard.
- Make sure that the cut end surface of the tube is a right angle without a scratch on the surface and deformations.
- Pull the tube lightly to check the complete installation.
- Avoid piping under the condition of tension and abruptly curved piping before the tube insertion

WARNINGS

- Avoid twisting or hitting the body of fitting when assembling. It may cause damage or air leakage.
- Make sure to check specifications before using fluid. It may cause damage or air leakage

MPC

Male Straight



MODEL (Φ-D-T)

Tube Metric - Thread R		Tube Inch - Thread R		Tube Inch - Thread NPT		Tube Metric - Thread M		Tube Metric - Thread G	
MPC 04M5	MPC 0804	PC 1/4 -01	PC 1/8-U	PC 1/8-N01	PC 1/8-N01	PC 06-M12	MPC 04G01	MPC 08G04	
MPC 04M6	MPC 1001	PC 1/4 -02	PC 1/8-N01	PC 1/8-N02	PC 06-M16	MPC 04G02	MPC 10G01		
MPC 0401	MPC 1002	PC 1/4 -03	PC 1/8-N02	PC 1/8-N03	PC 06-M22	MPC 04G03	MPC 10G02		
MPC 0402	MPC 1003	PC 1/4 -04	PC 1/8-N03	PC 1/8-N04	PC 08-M12	MPC 06G01	MPC 10G03		
MPC 0403	MPC 1004	PC 1/8 -01	PC 1/8-U	PC 1/8-N1	PC 08-M16	MPC 06G02	MPC 10G04		
MPC 06M5	MPC 1201	PC 1/8 -02	PC 1/8-N01	PC 1/8-N02	PC 08-M22	MPC 06G03	MPC 12G02		
MPC 06M6	MPC 1202	PC 1/8 -03	PC 1/8-N02	PC 1/8-N03	PC 10-M12	MPC 08G01	MPC 12G03		
MPC 0601	MPC 1203	PC 1/8 -01	PC 1/8-N03	PC 1/8-N04	PC 10-M14	MPC 08G02	MPC 12G04		
MPC 0602	MPC 1204	PC 1/8 -02	PC 1/8-U	PC 1/8-N01	PC 10-M16	MPC 08G03			
MPC 0603	MPC 1403	PC 1/8 -03	PC 1/8-N01	PC 1/8-N02	PC 10-M22				
MPC 0604	MPC 1404	PC 1/8 -04	PC 1/4-N02	PC 1/8-N03	PC 12-M12				
MPC 0801	MPC 1603	PC 1/2 -02	PC 1/4-N03	PC 1/2-N04	PC 12-M14				
MPC 0802	MPC 1604	PC 1/2 -03	PC 1/4-N04		PC 12-M16				
MPC 0803		PC 1/2 -04			PC 12-M22				

MPC-G

Male Straight



MPMM

Bulkhead Union



MODEL (Φ-D)

Tube Metric	Tube Inch
MPMM 04	PMM 1/16
MPMM 06	PMM 1/8
MPMM 08	PMM 1/4
MPMM 10	PMM 3/8
MPMM 12	PMM 1/2
MPMM 16	PMM 3/4

PMP

Plastic Bulkhead Union



MODEL (Φ-D)

Tube Metric	Tube Inch
PMP 04	
PMP 06	
PMP 08	
PMP 10	
PMP 12	

MPMF

Bulkhead Female Straight



MODEL (Φ-D-T)

Tube Metric - Thread Rc			Tube Inch - Thread NPT			Tube Metric - Thread G		
MPMF 04-01	MPMF 08-02	MPMF 12-02	PMF 1/8-N01	PMF 1/8-N03	MPMF 04-G01	MPMF 08-G03		
MPMF 04-02	MPMF 08-03	MPMF 12-03	PMF 1/8-N01	PMF 1/8-N02	MPMF 04-G02	MPMF 10-G02		
MPMF 04-03	MPMF 08-04	MPMF 12-04	PMF 1/8-N02	PMF 1/8-N03	MPMF 04-G03	MPMF 10-G03		
MPMF 06-01	MPMF 10-01		PMF 1/4-N01	PMF 1/2-N02	MPMF 06-G01	MPMF 10-G04		
MPMF 06-02	MPMF 10-02		PMF 1/4-N02	PMF 1/2-N03	MPMF 06-G02	MPMF 12-G02		
MPMF 06-03	MPMF 10-03		PMF 1/8-N01	PMF 1/2-N04	MPMF 06-G03	MPMF 12-G03		
MPMF 08-01	MPMF 10-04		PMF 1/8-N02		MPMF 08-G01	MPMF 12-G04		
					MPMF 08-G02			

MPL

Male Elbow
Swivel Rotating Type

MODEL (Φ-D-T)

Tube Metric - Thread R		Tube Inch - Thread R		Tube Inch - Thread NPT		Tube Metric - Thread M		Tube Metric - Thread G	
MPL 04M5	MPL 0803	PL 1/4-01	PL 1/8-N01	PL 1/8-N01	PL 1/8-N02	PL 06-M12	MPL 04G01	MPL 08G03	
MPL 04M6	MPL 0804	PL 1/4-02	PL 1/8-N02	PL 1/8-N02	PL 1/8-N03	PL 06-M16	MPL 04G02	MPL 08G04	
MPL 04M2	MPL 1002	PL 1/8-01	PL 1/8-N01	PL 1/8-N01	PL 1/8-N04	PL 06-M22	MPL 04G03	MPL 10G02	
MPL 04M3	MPL 1003	PL 1/8-02	PL 1/8-N02	PL 1/8-N02	PL 1/8-N01	PL 08-M12	MPL 06G01	MPL 10G03	
MPL 0403	MPL 1004	PL 1/8-03	PL 1/8-N03	PL 1/8-N03	PL 1/8-N02	PL 08-M16	MPL 06G02	MPL 10G04	
MPL 06M5	MPL 1202	PL 1/8-02	PL 1/8-N02	PL 1/8-N02	PL 1/8-N01	PL 08-M22	MPL 06G03	MPL 12G02	
MPL 06M6	MPL 1203	PL 1/8-01	PL 1/8-N03	PL 1/8-N03	PL 1/8-N04	PL 10-M12	MPL 08G01	MPL 12G03	
MPL 0601	MPL 1204	PL 1/8-02	PL 1/8-N04	PL 1/8-N04	PL 1/4-N01	PL 10-M14	MPL 08G02	MPL 12G04	
MPL 0602	MPL 1403	PL 1/8-03	PL 1/4-N01	PL 1/4-N01	PL 1/4-N02	PL 10-M16			
MPL 0603	MPL 1404	PL 1/8-04	PL 1/4-N02	PL 1/4-N02	PL 1/2-N03	PL 10-M22			
MPL 0801	MPL 1603	PL 1/2-02	PL 1/2-N03	PL 1/2-N03	PL 1/2-N04	PL 12-M12			
MPL 0802	MPL 1604	PL 1/2-03	PL 1/2-N04	PL 1/2-N04		PL 12-M14			
		PL 1/2-04				PL 12-M16			
						PL 12-M22			

MPL-G

Male Elbow



MPCF

Female Straight



MODEL (Φ-D-T)

Tube Metric - Thread Rc		Tube Inch - Thread Rc		Tube Inch - Thread NPT		Tube Metric - Thread G	
MPCF 04-M5	MPCF 08-03	PCF 1/4-01	PCF 1/8-N01	PCF 1/8-N03	MPCF 04-G01	MPCF 08-G04	
MPCF 06-M5	MPCF 08-04	PCF 1/4-02	PCF 1/8-N02	PCF 1/8-N04	MPCF 04-G02	MPCF 10-G01	
MPCF 04-01	MPCF 10-01	PCF 1/8-01	PCF 1/8-N01	PCF 1/8-N01	MPCF 04-G03	MPCF 10-G02	
MPCF 04-02	MPCF 10-02	PCF 1/8-02	PCF 1/8-N02	PCF 1/8-N02	MPCF 06-G01	MPCF 10-G03	
MPCF 04-03	MPCF 10-03	PCF 1/8-03	PCF 1/8-N03	PCF 1/8-N03	MPCF 06-G02	MPCF 10-G04	
MPCF 06-01	MPCF 10-04	PCF 1/8-03	PCF 1/4-N02	PCF 1/8-N04	MPCF 06-G03	MPCF 12-G02	
MPCF 06-02	MPCF 12-02	PCF 1/2-02	PCF 1/4-N03	PCF 1/2-N02	MPCF 08-G01	MPCF 12-G03	
MPCF 06-03	MPCF 12-03		PCF 1/8-N01	PCF 1/2-N03	MPCF 08-G02	MPCF 12-G04	
MPCF 06-04	MPCF 12-04		PCF 1/8-N02	PCF 1/2-N04	MPCF 08-G03		
MPCF 08-01	MPCF 16-03						
MPCF 08-02	MPCF 16-04						

MPCF-G

Female Straight



MPOC

Round Male Straight



MODEL (Φ-D-T)

Tube Metric - Thread R			Tube Inch - Thread R		Tube Inch - Thread NPT		
MPOC 04-M5	MPOC 06-02	MPOC 10-03	POC 1/4 -01	POC 5/32-U	POC 1/4 -N01	POC 1/8 -N03	
MPOC 04-M6	MPOC 06-03	MPOC 10-04	POC 1/4 -02	POC 1/2-N01	POC 1/4 -N02	POC 1/8 -N04	
MPOC 04-01	MPOC 06-01	MPOC 12-01	POC 1/8 -01	POC 3/8-N02	POC 1/8 -N01	POC 1/2 -N02	
MPOC 04-02	MPOC 06-02	MPOC 12-02	POC 1/8 -02	POC 1/2-N02	POC 1/8 -N02	POC 1/2 -N03	
MPOC 04-03	MPOC 06-03	MPOC 12-03	POC 1/8 -02	POC 1/2-N03	POC 1/8 -N01	POC 1/2 -N04	
MPOC 06-M5	MPOC 08-04	MPOC 12-04	POC 1/8 -03	POC 3/8-N02	POC 1/8 -N03	POC 1/2 -N01	
MPOC 06-M6	MPOC 10-01		POC 1/4 -U	POC 1/2-N02	POC 1/8 -N02		
MPOC 06-01	MPOC 10-02				POC 1/2-N03		

PL45

Male Elbow
Swivel Rotating Type

MODEL (ΦD-T)

Tube Metric-Thread R	Tube Inch-Thread R	Tube Inch-Thread NPT	Tube Metric-Thread G
PL45 04-M5	PL45 08-02	PL45 1/4-01	PL45 04-G01
PL45 04-M6	PL45 08-03	PL45 1/4-02	PL45 04-G02
PL45 04-M8	PL45 08-04	PL45 1/4-03	PL45 04-G03
PL45 04-M10	PL45 10-01	PL45 1/2-01	PL45 08-G01
PL45 04-M12	PL45 10-02	PL45 1/2-02	PL45 08-G02
PL45 06-M5	PL45 10-03	PL45 1/2-03	PL45 08-G03
PL45 06-M6	PL45 10-04	PL45 1/2-04	PL45 08-G04
PL45 06-M8	PL45 12-01	PL45 3/4-01	PL45 12-G01
PL45 06-M10	PL45 12-02	PL45 3/4-02	PL45 12-G02
PL45 06-M12	PL45 12-03	PL45 3/4-03	PL45 12-G03
PL45 08-M5	PL45 12-04	PL45 3/4-04	PL45 12-G04
PL45 08-M6			
PL45 08-M8			
PL45 08-M10			
PL45 08-M12			

MPLF

Female Elbow
Swivel Rotating Type

MODEL (ΦD-T)

Tube Metric-Thread Rc	Tube Inch-Thread NPT	Tube Metric-Thread G
MPLF 04-M5	PLF 1/8-01	MPLF 04-G01
MPLF 04-M6	PLF 1/8-02	MPLF 04-G02
MPLF 04-M8	PLF 1/8-03	MPLF 04-G03
MPLF 04-M10	PLF 1/8-04	MPLF 04-G04
MPLF 06-M5	PLF 1/4-01	MPLF 06-G01
MPLF 06-M6	PLF 1/4-02	MPLF 06-G02
MPLF 06-M8	PLF 1/4-03	MPLF 06-G03
MPLF 06-M10	PLF 1/4-04	MPLF 06-G04
MPLF 08-M5	PLF 1/2-01	MPLF 08-G01
MPLF 08-M6	PLF 1/2-02	MPLF 08-G02
MPLF 08-M8	PLF 1/2-03	MPLF 08-G03
MPLF 08-M10	PLF 1/2-04	MPLF 08-G04

MPLL

Extended Male Elbow
Swivel Rotating Type

MODEL (ΦD-T)

Tube Metric-Thread R	Tube Inch-Thread R	Tube Inch-Thread NPT	Tube Metric-Thread G
MPLL 04-M5	MPLL 08-04	MPLL 12-02	MPLL 04-G01
MPLL 04-M6	MPLL 08-05	MPLL 12-03	MPLL 04-G02
MPLL 04-M8	MPLL 08-06	MPLL 12-04	MPLL 04-G03
MPLL 04-M10	MPLL 08-07	MPLL 12-05	MPLL 04-G04
MPLL 04-M12	MPLL 08-08	MPLL 12-06	MPLL 04-G05
MPLL 06-M5	MPLL 10-01	MPLL 14-02	MPLL 06-G01
MPLL 06-M6	MPLL 10-02	MPLL 14-03	MPLL 06-G02
MPLL 06-M8	MPLL 10-03	MPLL 14-04	MPLL 06-G03
MPLL 06-M10	MPLL 10-04	MPLL 14-05	MPLL 06-G04
MPLL 06-M12	MPLL 10-05	MPLL 14-06	MPLL 06-G05

PL45-G

Male Elbow



PLLP

Extended Male Elbow
Swivel Rotating Type

MODEL (ΦD-T)

Tube Metric-Thread R	Tube Metric-Thread G
PLLP 04-M5	PLLP 08-02
PLLP 04-M6	PLLP 08-03
PLLP 04-M8	PLLP 08-04
PLLP 04-M10	PLLP 10-01
PLLP 04-M12	PLLP 10-02
PLLP 06-M5	PLLP 10-03
PLLP 06-M6	PLLP 10-04
PLLP 06-M8	PLLP 12-01
PLLP 06-M10	PLLP 12-02
PLLP 06-M12	PLLP 12-03
PLLP 08-M5	PLLP 12-04
PLLP 08-M6	PLLP 12-05
PLLP 08-M8	PLLP 12-06
PLLP 08-M10	PLLP 12-07
PLLP 08-M12	PLLP 12-08

MPT

Male Branch Tee
Swivel Rotating Type

MODEL (ΦD-T)

Tube Metric-Thread R	Tube Inch-Thread NPT	Tube Metric-Thread M	Tube Metric-Thread G
MPT 04M5	MPT 0802	PT 1/4-01	PT 1/8-N03
MPT 04M6	MPT 0803	PT 1/4-02	PT 1/8-N04
MPT 04M8	MPT 0804	PT 1/4-03	PT 1/8-N05
MPT 04M10	MPT 1002	PT 1/2-01	PT 3/8-N02
MPT 04M12	MPT 1003	PT 1/2-02	PT 3/8-N03
MPT 06M5	MPT 1004	PT 1/2-03	PT 3/8-N04
MPT 06M6	MPT 1202	PT 3/4-01	PT 1/2-N02
MPT 06M8	MPT 1203	PT 3/4-02	PT 1/2-N03
MPT 06M10	MPT 1204	PT 3/4-03	PT 1/2-N04
MPT 08M5	MPT 1603	PT 1-01	PT 1/2-N02
MPT 08M6	MPT 1604	PT 1-02	PT 1/2-N03
MPT 08M8	MPT 1605	PT 1-03	PT 1/2-N04
MPT 08M10	MPT 1606	PT 1-04	PT 1/2-N05

MPTF

Female Branch Tee
Swivel Rotating Type

MODEL (ΦD-T)

Tube Metric-Thread Rc	Tube Inch-Thread NPT	Tube Metric-Thread G
MPTF 04-M5	MPTF 08-02	MPTF 04-G01
MPTF 04-M6	MPTF 08-03	MPTF 04-G02
MPTF 04-M8	MPTF 08-04	MPTF 04-G03
MPTF 04-M10	MPTF 10-01	MPTF 04-G04
MPTF 04-M12	MPTF 10-02	MPTF 04-G05
MPTF 06-M5	MPTF 10-03	MPTF 06-G01
MPTF 06-M6	MPTF 10-04	MPTF 06-G02
MPTF 06-M8	MPTF 10-05	MPTF 06-G03
MPTF 06-M10	MPTF 12-01	MPTF 06-G04
MPTF 06-M12	MPTF 12-02	MPTF 06-G05
MPTF 08-M5	MPTF 12-03	MPTF 08-G01
MPTF 08-M6	MPTF 12-04	MPTF 08-G02
MPTF 08-M8	MPTF 12-05	MPTF 08-G03
MPTF 08-M10	MPTF 12-06	MPTF 08-G04
MPTF 08-M12	MPTF 12-07	MPTF 08-G05

PLLP-G

Extended Male Elbow
Swivel Rotating Type

MPT-G

Male Branch Tee
Swivel Rotating Type

MPTF-G

Female Branch Tee
Swivel Rotating Type

PST Male Run Tee Swivel Rotating Type



MODEL(ΦD-T)

Tube Metric - Thread R	Tube Inch - Thread R	Tube Inch - Thread NPT	Tube Metric - Thread M	Tube Metric - Thread G
PST 04-M5	PST 08-02	PST 1/4-01	PST 1/8-01	PST 04-G01
PST 04-M6	PST 08-03	PST 1/4-02	PST 1/8-02	PST 04-G02
PST 04-M8	PST 10-01	PST 1/2-01	PST 1/4-01	PST 04-G03
PST 04-M10	PST 10-02	PST 1/2-02	PST 1/4-02	PST 04-G04
PST 06-M5	PST 10-03	PST 1/2-03	PST 1/4-03	PST 06-G01
PST 06-M6	PST 10-04	PST 1/2-04	PST 1/4-04	PST 06-G02
PST 06-M8	PST 12-01	PST 3/4-01	PST 1/2-01	PST 06-G03
PST 06-M10	PST 12-02	PST 3/4-02	PST 1/2-02	PST 06-G04
PST 08-M5	PST 12-03	PST 3/4-03	PST 1/2-03	PST 08-G01
PST 08-M6	PST 12-04	PST 3/4-04	PST 1/2-04	PST 08-G02
PST 08-M8				
PST 08-M10				

PST-G Male Run Tee Swivel Rotating Type



PWT Male Y Swivel Rotating Type



MODEL(ΦD-T)

Tube Metric - Thread R	Tube Inch - Thread R	Tube Inch - Thread NPT	Tube Metric - Thread G
PWT 04-M5	PWT 08-02	PWT 1/4-01	PWT 04-G01
PWT 04-M6	PWT 08-03	PWT 1/4-02	PWT 04-G02
PWT 04-M8	PWT 10-01	PWT 1/2-01	PWT 04-G03
PWT 04-M10	PWT 10-02	PWT 1/2-02	PWT 04-G04
PWT 06-M5	PWT 10-03	PWT 1/2-03	PWT 06-G01
PWT 06-M6	PWT 10-04	PWT 1/2-04	PWT 06-G02
PWT 06-M8	PWT 12-01	PWT 3/4-01	PWT 06-G03
PWT 06-M10	PWT 12-02	PWT 3/4-02	PWT 06-G04
PWT 08-M5	PWT 12-03	PWT 3/4-03	PWT 08-G01
PWT 08-M6	PWT 12-04	PWT 3/4-04	PWT 08-G02
PWT 08-M8			
PWT 08-M10			

PWT-G Male Y Swivel Rotating Type



PLM Bulkhead Union Elbow



MODEL(ΦD)

Tube Metric	Tube Inch
PLM 04	PLM 1/8
PLM 06	PLM 1/4
PLM 08	PLM 1/2
PLM 10	PLM 3/4
PLM 12	PLM 1

PXT Male Double Y



MODEL(ΦD)

Tube Metric - Thread R	Tube Metric - Thread G
PXT 04-G01	PXT 04-G01
PXT 04-G02	PXT 04-G02
PXT 06-G01	PXT 06-G01
PXT 06-G02	PXT 06-G02

PXT-G Male Double Y



PKD Male Reducer Triple Branch Swivel Rotating Type



MODEL(ΦD1-ΦD2-T)

Tube Metric - Thread R	Tube Inch - Thread NPT	Tube Metric - Thread G
PKD 0604-01	PKD 1/4-01	PKD 0604-G01
PKD 0604-02	PKD 1/4-02	PKD 0604-G02
PKD 0604-03	PKD 1/4-03	PKD 0604-G03
PKD 0604-04	PKD 1/4-04	PKD 0604-G04
PKD 0605-01	PKD 1/2-01	PKD 0605-G01
PKD 0605-02	PKD 1/2-02	PKD 0605-G02
PKD 0605-03	PKD 1/2-03	PKD 0605-G03
PKD 0605-04	PKD 1/2-04	PKD 0605-G04
PKD 0606-01	PKD 3/4-01	PKD 0606-G01
PKD 0606-02	PKD 3/4-02	PKD 0606-G02
PKD 0606-03	PKD 3/4-03	PKD 0606-G03
PKD 0606-04	PKD 3/4-04	PKD 0606-G04

PKD-G Male Reducer Triple Branch Swivel Rotating Type



CAS



MODEL(ΦD)

Tube Metric	Tube Inch
CAS 04	CAS 1/8
CAS 06	CAS 1/4
CAS 08	CAS 3/8
CAS 10	CAS 1/2
CAS 12	CAS 5/8

MPH Male Barjo Swivel Rotating Type



MODEL(ΦD-T)

Tube Metric - Thread R	Tube Inch - Thread R	Tube Inch - Thread NPT	Tube Metric - Thread G
MPH 03-M5	MPH 08-01	PH 1/4-M5	PH 1/4-N03
MPH 04-M5	MPH 08-02	PH 1/4-01	PH 1/4-N01
MPH 04-M6	MPH 08-03	PH 1/4-02	PH 1/4-N02
MPH 04-M8	MPH 08-04	PH 1/4-03	PH 1/4-N03
MPH 04-M10	MPH 10-01	PH 1/2-01	PH 1/2-N01
MPH 06-M5	MPH 10-02	PH 1/2-02	PH 1/2-N02
MPH 06-M6	MPH 10-03	PH 1/2-03	PH 1/2-N03
MPH 06-M8	MPH 10-04	PH 1/2-04	PH 1/2-N04
MPH 06-M10	MPH 12-01	PH 3/4-01	PH 3/4-N01
MPH 08-M5	MPH 12-02	PH 3/4-02	PH 3/4-N02
MPH 08-M6	MPH 12-03	PH 3/4-03	PH 3/4-N03
MPH 08-M8	MPH 12-04	PH 3/4-04	PH 3/4-N04

MPHF Female Barjo Swivel Rotating Type



MODEL(ΦD-T)

Tube Metric - Thread R	Tube Inch - Thread R	Tube Inch - Thread NPT	Tube Metric - Thread G
MPHF 03-M5	MPHF 08-01	PHF 1/4-M5	PHF 1/4-N03
MPHF 04-M5	MPHF 08-02	PHF 1/4-01	PHF 1/4-N01
MPHF 04-M6	MPHF 08-03	PHF 1/4-02	PHF 1/4-N02
MPHF 04-M8	MPHF 08-04	PHF 1/4-03	PHF 1/4-N03
MPHF 06-M5	MPHF 10-01	PHF 1/2-01	PHF 1/2-N01
MPHF 06-M6	MPHF 10-02	PHF 1/2-02	PHF 1/2-N02
MPHF 06-M8	MPHF 10-03	PHF 1/2-03	PHF 1/2-N03
MPHF 06-M10	MPHF 12-01	PHF 3/4-01	PHF 3/4-N01
MPHF 08-M5	MPHF 12-02	PHF 3/4-02	PHF 3/4-N02
MPHF 08-M6	MPHF 12-03	PHF 3/4-03	PHF 3/4-N03
MPHF 08-M8	MPHF 12-04	PHF 3/4-04	PHF 3/4-N04
MPHF 08-M10	MPHF 14-01	PHF 1-01	PHF 1-N01
MPHF 10-M5	MPHF 14-02	PHF 1-02	PHF 1-N02
MPHF 10-M6	MPHF 14-03	PHF 1-03	PHF 1-N03
MPHF 10-M8	MPHF 14-04	PHF 1-04	PHF 1-N04

MPH-G Male Barjo Swivel Rotating Type



MPHF-G Female Barjo Swivel Rotating Type



PHL(2)

Double Universal Elbow



MODEL(ΦD-T)

Tube Metric - Thread R			Tube Metric - Thread G		
PHL 04-01(2)	PHL 06-04(2)	PHL 10-03(2)	PHL 04-G01(2)	PHL 06-G04(2)	PHL 10-G03(2)
PHL 04-02(2)	PHL 06-01(2)	PHL 10-04(2)	PHL 04-G02(2)	PHL 06-G01(2)	PHL 10-G04(2)
PHL 04-03(2)	PHL 06-02(2)	PHL 12-02(2)	PHL 04-G03(2)	PHL 06-G02(2)	PHL 12-G02(2)
PHL 04-04(2)	PHL 06-03(2)	PHL 12-03(2)	PHL 04-G04(2)	PHL 06-G03(2)	PHL 12-G03(2)
PHL 06-01(2)	PHL 06-04(2)	PHL 12-04(2)	PHL 06-G01(2)	PHL 06-G04(2)	PHL 12-G04(2)
PHL 06-02(2)	PHL 10-01(2)		PHL 06-G02(2)	PHL 10-G01(2)	
PHL 06-03(2)			PHL 06-G03(2)	PHL 10-G02(2)	

PHL-G(2)

Double Universal Elbow



PHL(3)

Triple Universal Elbow



MODEL(ΦD-T)

Tube Metric - Thread R			Tube Metric - Thread G		
PHL 04-01(3)	PHL 06-04(3)	PHL 10-03(3)	PHL 04-G01(3)	PHL 06-G04(3)	PHL 10-G03(3)
PHL 04-02(3)	PHL 06-01(3)	PHL 10-04(3)	PHL 04-G02(3)	PHL 06-G01(3)	PHL 10-G04(3)
PHL 04-03(3)	PHL 06-02(3)	PHL 12-02(3)	PHL 04-G03(3)	PHL 06-G02(3)	PHL 12-G02(3)
PHL 04-04(3)	PHL 06-03(3)	PHL 12-03(3)	PHL 04-G04(3)	PHL 06-G03(3)	PHL 12-G03(3)
PHL 06-01(3)	PHL 06-04(3)	PHL 12-04(3)	PHL 06-G01(3)	PHL 06-G04(3)	PHL 12-G04(3)
PHL 06-02(3)	PHL 10-01(3)		PHL 06-G02(3)	PHL 10-G01(3)	
PHL 06-03(3)	PHL 10-02(3)		PHL 06-G03(3)	PHL 10-G02(3)	

PHL-G(3)

Triple Universal Elbow



PHT(2)

Double Universal Tee



MODEL(ΦD-T)

Tube Metric - Thread R			Tube Metric - Thread G		
PHT 04-01(2)	PHT 06-04(2)	PHT 10-03(2)	PHT 04-G01(2)	PHT 06-G04(2)	PHT 10-G03(2)
PHT 04-02(2)	PHT 06-01(2)	PHT 10-04(2)	PHT 04-G02(2)	PHT 06-G01(2)	PHT 10-G04(2)
PHT 04-03(2)	PHT 06-02(2)	PHT 12-02(2)	PHT 04-G03(2)	PHT 06-G02(2)	PHT 12-G02(2)
PHT 04-04(2)	PHT 06-03(2)	PHT 12-03(2)	PHT 04-G04(2)	PHT 06-G03(2)	PHT 12-G03(2)
PHT 06-01(2)	PHT 06-04(2)	PHT 12-04(2)	PHT 06-G01(2)	PHT 06-G04(2)	PHT 12-G04(2)
PHT 06-02(2)	PHT 10-01(2)		PHT 06-G02(2)	PHT 10-G01(2)	
PHT 06-03(2)	PHT 10-02(2)		PHT 06-G03(2)	PHT 10-G02(2)	

PHT-G(2)

Double Universal Tee



PHT(3)

Triple Universal Tee



MODEL(ΦD-T)

Tube Metric - Thread R			Tube Metric - Thread G		
PHT 04-01(3)	PHT 06-04(3)	PHT 10-03(3)	PHT 04-G01(3)	PHT 06-G04(3)	PHT 10-G03(3)
PHT 04-02(3)	PHT 06-01(3)	PHT 10-04(3)	PHT 04-G02(3)	PHT 06-G01(3)	PHT 10-G04(3)
PHT 04-03(3)	PHT 06-02(3)	PHT 12-02(3)	PHT 04-G03(3)	PHT 06-G02(3)	PHT 12-G02(3)
PHT 04-04(3)	PHT 06-03(3)	PHT 12-03(3)	PHT 04-G04(3)	PHT 06-G03(3)	PHT 12-G03(3)
PHT 06-01(3)	PHT 06-04(3)	PHT 12-04(3)	PHT 06-G01(3)	PHT 06-G04(3)	PHT 12-G04(3)
PHT 06-02(3)	PHT 10-01(3)		PHT 06-G02(3)	PHT 10-G01(3)	
PHT 06-03(3)	PHT 10-02(3)		PHT 06-G03(3)	PHT 10-G02(3)	

PHT-G(3)

Triple Universal Tee



PHT(1)

Single Universal Tee



MODEL(ΦD-T)

Tube Metric - Thread R			Tube Metric - Thread G		
PHT 04-01(1)	PHT 06-04(1)	PHT 10-03(1)	PHT 04-G01(1)	PHT 06-G04(1)	PHT 10-G03(1)
PHT 04-02(1)	PHT 06-01(1)	PHT 10-04(1)	PHT 04-G02(1)	PHT 06-G01(1)	PHT 10-G04(1)
PHT 04-03(1)	PHT 06-02(1)	PHT 12-02(1)	PHT 04-G03(1)	PHT 06-G02(1)	PHT 12-G02(1)
PHT 04-04(1)	PHT 06-03(1)	PHT 12-03(1)	PHT 04-G04(1)	PHT 06-G03(1)	PHT 12-G03(1)
PHT 06-01(1)	PHT 06-04(1)	PHT 12-04(1)	PHT 06-G01(1)	PHT 06-G04(1)	PHT 12-G04(1)
PHT 06-02(1)	PHT 10-01(1)		PHT 06-G02(1)	PHT 10-G01(1)	
PHT 06-03(1)	PHT 10-02(1)		PHT 06-G03(1)	PHT 10-G02(1)	

PHT-G(1)

Single Universal Tee



PA

Branch A



MODEL(ΦD-T)

Tube Metric - Thread R	Tube Metric - Thread G
PA 04-M5	PA 06-G01
PA 06-01	PA 06-G02
PA 06-02	PA 10-G02
PA 06-03	PA 10-G03
PA 10-02	PA 12-G03
PA 10-03	PA 12-G04
PA 12-03	
PA 12-04	

PA-G

Branch A



PAF

Female Branch A



MODEL(ΦD-T)

Tube Metric - Thread R	Tube Metric - Thread G
PAF 04-M5	PAF 06-G01
PAF 06-01	PAF 06-G02
PAF 06-02	PAF 10-G02
PAF 10-02	PAF 10-G03
PAF 10-03	PAF 12-G03
PAF 12-03	PAF 12-G04
PAF 12-04	

PAF-G

Female Branch A



PAT(2)

Double Branch A



MODEL(ΦD-T)

Tube Metric - Thread R			Tube Metric - Thread G		
PAT 04-01(2)	PAT 06-04(2)	PAT 10-03(2)	PAT 04-G01(2)	PAT 06-G04(2)	PAT 10-G03(2)
PAT 04-02(2)	PAT 06-01(2)	PAT 10-04(2)	PAT 04-G02(2)	PAT 06-G01(2)	PAT 10-G04(2)
PAT 04-03(2)	PAT 06-02(2)	PAT 12-02(2)	PAT 04-G03(2)	PAT 06-G02(2)	PAT 12-G02(2)
PAT 04-04(2)	PAT 06-03(2)	PAT 12-03(2)	PAT 04-G04(2)	PAT 06-G03(2)	PAT 12-G03(2)
PAT 06-01(2)	PAT 06-04(2)	PAT 12-04(2)	PAT 06-G01(2)	PAT 06-G04(2)	PAT 12-G04(2)
PAT 06-02(2)	PAT 10-01(2)		PAT 06-G02(2)	PAT 10-G01(2)	
PAT 06-03(2)	PAT 10-02(2)		PAT 06-G03(2)	PAT 10-G02(2)	

PAT-G(2)

Double Branch A



PAT(3)

Triple Branch A



MODEL(ΦD-T)

Tube Metric - Thread R			Tube Metric - Thread G		
PAT 04-01(3)	PAT 06-04(3)	PAT 10-03(3)	PAT 04-G01(3)	PAT 06-G04(3)	PAT 10-G03(3)
PAT 04-02(3)	PAT 06-01(3)	PAT 10-04(3)	PAT 04-G02(3)	PAT 06-G01(3)	PAT 10-G04(3)
PAT 04-03(3)	PAT 06-02(3)	PAT 12-02(3)	PAT 04-G03(3)	PAT 06-G02(3)	PAT 12-G02(3)
PAT 04-04(3)	PAT 06-03(3)	PAT 12-03(3)	PAT 04-G04(3)	PAT 06-G03(3)	PAT 12-G03(3)
PAT 06-01(3)	PAT 06-04(3)	PAT 12-04(3)	PAT 06-G01(3)	PAT 06-G04(3)	PAT 12-G04(3)
PAT 06-02(3)	PAT 10-01(3)		PAT 06-G02(3)	PAT 10-G01(3)	
PAT 06-03(3)	PAT 10-02(3)		PAT 06-G03(3)	PAT 10-G02(3)	

PAT-G(3)

Triple Branch A



MPUC

Union Straight



MODEL(ΦD)

Tube Metric	Tube Inch
MPUC 04	PUC 1/32
MPUC 06	PUC 1/16
MPUC 08	PUC 1/8
MPUC 10	PUC 1/4
MPUC 12	PUC 3/8
MPUC 14	PUC 1/2
MPUC 16	

MPUL

Union Elbow



MODEL(ΦD)

Tube Metric	Tube Inch
MPUL 04	PUL 1/32
MPUL 06	PUL 1/16
MPUL 08	PUL 1/8
MPUL 10	PUL 1/4
MPUL 12	PUL 3/8
	PUL 1/2

MPUT

Union Tee



MODEL(ΦD)

Tube Metric	Tube Inch
MPUT 04	PUL 1/32
MPUT 06	PUL 1/16
MPUT 08	PUL 1/8
MPUT 10	PUL 1/4
MPUT 12	PUL 3/8
MPUT 14	PUL 1/2
MPUT 16	

MPY

Union Y



MODEL(ΦD)

Tube Metric	Tube Inch
MPY 04	PY 1/32
MPY 06	PY 1/16
MPY 08	PY 1/8
MPY 10	PY 1/4
MPY 12	PY 3/8
MPY 16	PY 1/2

MPW

Reducer Y



MODEL(ΦD1-ΦD2)

Tube Metric	Tube Inch
MPW 0604	PW 1/32 - 1/32
MPW 0606	PW 1/16 - 1/16
MPW 0608	PW 1/8 - 1/8
MPW 0610	PW 1/4 - 1/4
MPW 0612	PW 3/8 - 3/8
MPW 0616	PW 1/2 - 1/2

MPG

Reducer



MODEL(ΦD1-ΦD2)

Tube Metric	Tube Inch
MPG 0604	PG 1/32 - 1/32
MPG 0606	PG 1/16 - 1/16
MPG 0608	PG 1/8 - 1/8
MPG 0610	PG 1/4 - 1/4
MPG 0612	PG 3/8 - 3/8
MPG 0616	PG 1/2 - 1/2

PGT

Reducer Tee



MODEL(ΦD1-ΦD2)

Tube Metric	Tube Inch
PGT 0604	PGT 1/32 - 1/32
PGT 0606	PGT 1/16 - 1/16
PGT 0608	PGT 1/8 - 1/8
PGT 0610	PGT 1/4 - 1/4
PGT 0612	PGT 3/8 - 3/8
PGT 0616	PGT 1/2 - 1/2

PGT

Expander Tee



MODEL(ΦD1-ΦD2)

Tube Metric	Tube Inch
PGT 0606	PGT 1/16 - 1/16
PGT 0608	PGT 1/8 - 1/8
PGT 0610	PGT 1/4 - 1/4
PGT 0612	PGT 3/8 - 3/8

MPLJ

Plug-In Elbow



MODEL(ΦD)

Tube Metric	Tube Inch
MPLJ 04	PLJ 1/32
MPLJ 06	PLJ 1/16
MPLJ 08	PLJ 1/8
MPLJ 10	PLJ 1/4
MPLJ 12	PLJ 3/8
MPLJ 16	PLJ 1/2
MPLJ 0604	PLJ 1/32 - 1/4
MPLJ 0606	PLJ 1/16 - 1/4
MPLJ 0608	PLJ 1/8 - 1/4
MPLJ 0610	PLJ 1/4 - 1/4
MPLJ 0612	PLJ 3/8 - 1/2
MPLJ 0616	PLJ 1/2 - 1/2

PGJ

Plug-In Reducer



MODEL(ΦD1-ΦD2)

Tube Metric	Tube Inch
PGJ 0406	PGJ 1/32 - 1/16
PGJ 0604	PGJ 1/16 - 1/32
PGJ 0606	PGJ 1/8 - 1/16
PGJ 0608	PGJ 1/8 - 1/8
PGJ 0610	PGJ 1/4 - 1/8
PGJ 0612	PGJ 3/8 - 1/4
PGJ 0616	PGJ 1/2 - 1/4
PGJ 0618	PGJ 5/8 - 1/4
PGJ 0620	PGJ 3/4 - 1/4
PGJ 0622	PGJ 7/8 - 1/4
PGJ 0624	PGJ 1 - 1/4

PYJ

Plug-In Y



MODEL(ΦD)

Tube Metric	Tube Inch
PYJ 04	PYJ 1/32
PYJ 06	PYJ 1/16
PYJ 08	PYJ 1/8
PYJ 10	PYJ 1/4
PYJ 12	PYJ 3/8
PYJ 16	PYJ 1/2

PUJ
Tube Splicer

MODEL (ΦD)

Tube Metric	Tube Inch
PUJ 04	PUJ 1/32
PUJ 06	PUJ 1/16
PUJ 08	PUJ 1/8
PUJ 10	PUJ 3/16
PUJ 12	PUJ 1/4
PUJ 16	PUJ 1/2

PWJ
Plug-In Reducer Y

MODEL (ΦD1-ΦD2)

Tube Metric	Tube Inch
PWJ 0604	PWJ 1/16 - 1/32
PWJ 0806	PWJ 1/16 - 1/8
PWJ 1008	PWJ 1/8 - 1/4
PWJ 1210	PWJ 1/8 - 1/2

MPCP
Coupler Plug

MODEL (ΦD1-ΦD2)

Tube Metric	Tube Inch
MPCP 04	PCP 1/32
MPCP 06	PCP 1/16
MPCP 08	PCP 1/8
MPCP 10	PCP 1/4
MPCP 12	PCP 1/2
MPCP 16	PCP 1/2

PKG
Reducer Triple Branch Union

MODEL (ΦD1-ΦD2)

Tube Metric	Tube Inch
PKG 0604	PKG 1/16 - 1/32
PKG 0804	PKG 1/8 - 1/32
PKG 0806	PKG 1/8 - 1/16
PKG 1006	PKG 1/4 - 1/16
PKG 1008	PKG 1/4 - 1/8
	PKG 1/2 - 1/16

PXG
Reducer Double Y

MODEL (ΦD1-ΦD2)

Tube Metric	Tube Inch
PXG 06 04	
PXG 08 06	

PXJ
Plug-In Reducer Double Y

MODEL (ΦD1-ΦD2)

Tube Metric	Tube Inch
PXJ 06 04	
PXJ 08 06	

PSJ
Plug-In Run Tee

MODEL (ΦD1-ΦD2)

Tube Metric	Tube Inch
PSJ 04	PSJ 1/32
PSJ 06	PSJ 1/16
PSJ 08	PSJ 1/8
PSJ 10	PSJ 3/16
PSJ 12	PSJ 1/4
PSJ 0604	PSJ 1/2
PSJ 0806	PSJ 1/4 - 1/32
PSJ 1008	PSJ 1/8 - 1/4
PSJ 1210	PSJ 1/8 - 1/2
	PSJ 1/2 - 3/8

PTJ
Plug-In Branch Tee

MODEL (ΦD1-ΦD2)

Tube Metric	Tube Inch
PTJ 04	PTJ 1/32
PTJ 06	PTJ 1/16
PTJ 08	PTJ 1/8
PTJ 10	PTJ 3/16
PTJ 12	PTJ 1/4
PTJ 0604	PTJ 1/2
PTJ 0806	PTJ 1/4 - 1/32
PTJ 1008	PTJ 1/8 - 1/4
PTJ 1210	PTJ 1/8 - 1/2
	PTJ 1/2 - 3/8

PIG
Reducer Tube Splicer

MODEL (ΦD1-ΦD2)

Tube Metric	Tube Inch
PIG 0604	PIG 1/16 - 1/32
PIG 0804	PIG 1/8 - 1/32
PIG 0806	PIG 1/8 - 1/16
PIG 1006	PIG 1/4 - 1/16
PIG 1008	PIG 1/4 - 1/8
PIG 1208	PIG 1/2 - 1/16
PIG 1210	PIG 1/2 - 1/8
PIG 1612	

PKJ
Plug-In Reducer Triple Branch

MODEL (ΦD1-ΦD2)

Tube Metric	Tube Inch
PKJ 0604	PKJ 1/16 - 1/32
PKJ 0804	PKJ 1/8 - 1/32
PKJ 0806	PKJ 1/8 - 1/16
PKJ 1006	PKJ 1/4 - 1/16
PKJ 1008	PKJ 1/4 - 1/8
	PKJ 1/2 - 1/16

PMG

MODEL (ΦD)

Tube Metric	Tube Inch
PMG 0604	
PMG 1006	
PMG 1008	
PMG 1208	

PP
Plug

MODEL (ΦD)

Tube Metric	Tube Inch
PP 04	PP 1/32
PP 06	PP 1/16
PP 08	PP 1/8
PP 10	PP 3/16
PP 12	PP 1/4
PP 16	PP 1/2

PPF
Cap

MODEL (ΦD)

Tube Metric	Tube Inch
PPF 04	PPF 1/32
PPF 06	PPF 1/16
PPF 08	PPF 1/8
PPF 10	PPF 3/16
PPF 12	PPF 1/4
PPF 16	PPF 1/2

PZA
Union Cross

MODEL (ΦD)

Tube Metric	Tube Inch
PZA 04	PZA 1/32
PZA 06	PZA 1/16
PZA 08	PZA 1/8
PZA 10	PZA 3/16
PZA 12	PZA 1/4
	PZA 1/2

COMPACT ONE-TOUCH FITTINGS



Product Code System

METRIC - BSP(F/R)			
PC 06-01-C			
COMPACT ONE-TOUCH FITTING	TUBE DIA CODE SIZE	THREAD SIZE METRIC THREAD CODE SIZE	COMPACT Nickel
	03 Ø3	M3 M3×0.5	
	04 Ø4	M4 M4×0.5	
	06 Ø6	M6 M6×1.0	
		R/PTT THREAD CODE SIZE	
		3/8 1/8	

INCH - BSP(F/R)			
PC-1/4-01-C			
COMPACT ONE-TOUCH FITTING	TUBE DIA CODE SIZE	THREAD SIZE INCH THREAD CODE SIZE	COMPACT Nickel
	1/4 Ø1/4	M3 M3×0.5	
	1/2 Ø1/2	M4 M4×0.5	
	3/8 Ø3/8	M6 M6×1.0	
		R/PTT THREAD CODE SIZE	
		3/8 1/8	

METRIC - BSP(F/R)			
PC 06-G01-C			
COMPACT ONE-TOUCH FITTING	TUBE DIA CODE SIZE	THREAD SIZE G/PTT THREAD CODE SIZE	
	04 Ø4	G1 G 1/8	
	06 Ø6		

INCH - NPT			
PC-1/4-NI-C			
COMPACT ONE-TOUCH FITTING	TUBE DIA CODE SIZE	THREAD SIZE UNF THREAD CODE SIZE	
	1/4 Ø1/4	1/8 1/8-28UNF	
	1/2 Ø1/2	1/4 1/4-20UNF	
		NPT THREAD CODE SIZE	
		1/8 NPT 1/8	
		1/4 NPT 1/4	

Uses

- Compact type one-touch joints used in narrow spaces
- Used for various environments to meet all needs

Features

- Easy installation and disconnection by one-touch
- Smaller volume ratio and smaller O.D. but the same flow rate compared the general type
- Electroless nickel plating type provides excellent corrosion resistance
- Oval sleeves are designed to install in narrow spaces
- The screws are O-ringed or Teflon-treated.
- It is suitable for small devices and narrow-space piping.

Specifications

Fluid type	Air/No other gases or liquids
Working pressure	0~150PSI / 0~9.8kgf/cm ² (0~980kPa) *In combination with the applied tube, it is based on the maximum operating pressure of the tube.
Negative pressure	-29.5 in Hg / -750mmHg(-750Torr)
Working temperature	32~140° F / 0~60° C
Applicable Tube	Polyurethane and Nylon


Structural drawing



- All fittings are brass body type and electroless nickel(EN) plating, thus, provides excellent corrosion resistance.
- Oval sleeves are easy to install and disconnect.

POC Models	Use a hexagonal wrench to tighten internal hexagonal part. POC products cannot be fastened with other tools since the outside of the body is circular.
PL Models	
PLL Models	Rotation of plastic body makes the tube piping efficient.

Example of uses



CAUTIONS

- Be sure to read "Caution", "Warning", "Common Safety Instructions"(pp. 25) and precautions of using fitting products before use.
- Make sure to check "Recommended Tightening Torque"(pp.26)
- It is recommended to rotate the fitting 3-5 times using a tool after tightening by hand. Screws will break if it pushes too hard.
- Make sure that the out end surface of the tube is a right angle without a scratch on the surface and deformations.
- Put the tube lightly to check the complete installation.
- Avoid piping under the condition of tension and abruptly curved piping before the tube insertion

WARNINGS

- Avoid twisting or hitting the body of fitting when assembling. It may cause damage or air leakage.
- Make sure to check specifications before using fluid. It may cause damage or air leakage

PC-C

Male Straight



MODEL(ΦD-T)

Tube Metric -Thread R		Tube Inch-Thread R		Tube Inch -Thread NPT		Tube Metric-Thread G
PC 03-M3C	PC 04-M6C	PC 1/8-M3C	PC 1/8-M6C	PC 1/8-UC	PC 1/8-N0C	PC 04-G01C
PC 03-M5C	PC 04-01C	PC 1/8-M5C	PC 1/8-01C	PC 1/8-N0C	PC 1/8-N1C	PC 06-G01C
PC 03-M6C	PC 06-M5C	PC 1/8-M6C	PC 1/4-M5C	PC 1/8-N1C	PC 1/4-UC	
PC 03-01C	PC 06-M6C	PC 1/8-01C	PC 1/4-M6C	PC 1/8-N2C	PC 1/4-N0C	
PC 04-M3C	PC 06-01C	PC 1/8-M3C	PC 1/4-M3C	PC 1/8-UC	PC 1/4-N1C	
PC 04-M5C		PC 1/8-M5C				

PC-G-C

Male Straight



PMM-C

Bulkhead Union



MODEL(ΦD)

Tube Metric	Tube Inch
PMM 03C	
PMM 04C	
PMM 06C	

PLJ-C



MODEL(ΦD)

Tube Metric	Tube Inch-Thread NPT
PLJ 03C	PLJ 1/8 C
PLJ 04C	PLJ 1/8 C
PLJ 06C	PLJ 1/4 C

PCF-C

Female Straight



MODEL(ΦD-T)

Tube Metric -Thread Rc		Tube Inch-Thread Rc		Tube Inch-Thread NPT	
PCF 03-M3C	PCF 04-M6C	PCF 1/8-M3C	PCF 1/8-M6C	PCF 1/8-UC	PCF 1/8-N0C
PCF 03-M5C	PCF 04-01C	PCF 1/8-M5C	PCF 1/8-01C	PCF 1/8-N0C	PCF 1/8-N1C
PCF 03-M6C	PCF 06-M5C	PCF 1/8-M6C	PCF 1/4-M5C	PCF 1/8-N1C	PCF 1/4-UC
PCF 04-M3C	PCF 06-M6C	PCF 1/8-01C	PCF 1/4-M6C	PCF 1/8-N2C	PCF 1/4-N0C
PCF 04-M5C	PCF 06-01C	PCF 1/8-M3C	PCF 1/4-01C	PCF 1/8-UC	PCF 1/4-N1C
		PCF 1/8-M5C			

PL-C

Male Elbow



MODEL(ΦD-T)

Tube Metric -Thread R		Tube Inch-Thread R		Tube Inch -Thread NPT		Tube Metric-Thread G
PL 03-M3C	PL 04-01C	PL 1/8-M3C	PL 1/8-M6C	PL 1/8-UC	PL 1/8-N1C	PL 04-G01C
PL 03-M5C	PL 06-M5C	PL 1/8-M5C	PL 1/8-01C	PL 1/8-N0C	PL 1/4-UC	PL 06-G01C
PL 03-M6C	PL 06-M6C	PL 1/8-M6C	PL 1/4-M5C	PL 1/8-N1C	PL 1/4-N0C	
PL 04-M3C	PL 06-01C	PL 1/8-01C	PL 1/4-M6C	PL 1/8-UC	PL 1/4-N1C	
PL 04-M5C		PL 1/8-M3C	PL 1/4-01C	PL 1/8-N0C		
PL 04-M6C		PL 1/8-M5C				

PL-G-C

Male Elbow



POC-C

Round Male Straight



MODEL(ΦD-T)

Tube Metric -Thread R		Tube Inch-Thread R		Tube Inch-Thread NPT	
POC 03-M3C	POC 04-01C	POC 1/8-M3C	POC 1/8-M6C	POC 1/8-UC	POC 1/4-UC
POC 03-M5C	POC 06-M5C	POC 1/8-M5C	POC 1/8-01C	POC 1/8-N0C	POC 1/4-N0C
POC 03-M6C	POC 06-M6C	POC 1/8-M6C	POC 1/4-M5C	POC 1/8-N1C	POC 1/4-N1C
POC 04-M3C	POC 06-01C	POC 1/8-01C	POC 1/4-M6C	POC 1/8-UC	
POC 04-M5C		POC 1/8-M3C	POC 1/4-01C	POC 1/8-N0C	
POC 04-M6C		POC 1/8-M5C		POC 1/8-N1C	

PLL-C

Extended Male Elbow



MODEL(ΦD-T)

Tube Metric -Thread R		Tube Inch-Thread R		Tube Inch-Thread NPT	
PLL 03-M3C	PLL 04-01C	PLL 1/8-M3C	PLL 1/8-M6C	PLL 1/8-UC	PLL 1/4-UC
PLL 03-M5C	PLL 06-M5C	PLL 1/8-M5C	PLL 1/8-01C	PLL 1/8-N0C	PLL 1/4-N0C
PLL 03-M6C	PLL 06-M6C	PLL 1/8-M6C	PLL 1/4-M5C	PLL 1/8-N1C	PLL 1/4-N1C
PLL 04-M3C	PLL 06-01C	PLL 1/8-01C	PLL 1/4-M6C	PLL 1/8-UC	
PLL 04-M5C		PLL 1/8-M3C	PLL 1/4-01C	PLL 1/8-N0C	
PLL 04-M6C		PLL 1/8-M5C		PLL 1/8-N1C	

PT-C

Male Branch Tee



MODEL(ΦD-T)

Tube Metric - Thread R		Tube Inch-Thread R		Tube Inch-Thread NPT	
PT 03-M3C	PT 04-01C	PT 1/8-M3C	PT 1/8-M6C	PT 1/8-UC	PT 1/8-UC
PT 03-M3C	PT 06-M5C	PT 1/8-M5C	PT 1/8-01C	PT 1/8-N6C	PT 1/8-N6C
PT 03-M6C	PT 06-M6C	PT 1/8-M6C	PT 1/8-M5C	PT 1/8-N1C	PT 1/8-N1C
PT 04-M3C	PT 06-01C	PT 1/8-01C	PT 1/8-M6C	PT 1/8-UC	PT 1/8-UC
PT 04-M3C		PT 1/8-M3C	PT 1/8-01C	PT 1/8-N6C	PT 1/8-N6C
PT 04-M6C		PT 1/8-M5C		PT 1/8-N1C	PT 1/8-N1C

PUT-C

Union Tee



MODEL(ΦD)

Tube Metric	Tube Inch
PUT 03C	PUT 1/8 C
PUT 04C	PUT 1/16 C
PUT 06C	PUT 1/8 C

PG-C

Reducer



MODEL(ΦD1-ΦD2)

Tube Metric	Tube Inch
PG 04-03C	PG 1/16 - 1/8 C
PG 06-03C	PG 1/8 - 1/8 C
PG 06-04C	PG 1/8 - 1/16 C

PST-C

Male Run Tee



MODEL(ΦD-T)

Tube Metric - Thread R		Tube Inch-Thread R		Tube Inch-Thread NPT	
PST 03-M3C	PST 04-01C	PST 1/8-M3C	PST 1/8-M6C	PST 1/8-UC	PST 1/8-UC
PST 03-M5C	PST 06-M5C	PST 1/8-M5C	PST 1/8-01C	PST 1/8-N6C	PST 1/8-N6C
PST 03-M6C	PST 06-M6C	PST 1/8-M6C	PST 1/8-M5C	PST 1/8-N1C	PST 1/8-N1C
PST 04-M3C	PST 06-01C	PST 1/8-01C	PST 1/8-M6C	PST 1/8-UC	PST 1/8-UC
PST 04-M5C		PST 1/8-M3C	PST 1/8-01C	PST 1/8-N6C	PST 1/8-N6C
PST 04-M6C		PST 1/8-M5C		PST 1/8-N1C	PST 1/8-N1C

PY-C

Union Y



MODEL(ΦD)

Tube Metric	Tube Inch
PY 03C	
PY 04C	
PY 06C	

PW-C

Reducer Y



MODEL(ΦD1-ΦD2)

Tube Metric	Tube Inch
PW 04-03C	PW 1/16 - 1/8 C
PW 06-03C	PW 1/8 - 1/8 C
PW 06-04C	PW 1/8 - 1/16 C

PUC-C

Union Straight



MODEL(ΦD)

Tube Metric	Tube Inch
PUC 03C	PUC 1/8 C
PUC 04C	PUC 1/16 C
PUC 06C	PUC 1/8 C

PUL-C

Union Elbow



MODEL(ΦD)

Tube Metric	Tube Inch-Thread NPT
PUL 03C	PUL 1/8 C
PUL 04C	PUL 1/16 C
PUL 06C	PUL 1/8 C

PGJ-C

Plug-in Reducer



MODEL(ΦD1-ΦD2)

Tube Metric	Tube Inch
PGJ 04-03C	PGJ 1/16 - 1/8 C
PGJ 06-03C	PGJ 1/8 - 1/8 C
PGJ 06-04C	PGJ 1/8 - 1/16 C

PP-C

Plug



MODEL(ΦD1-ΦD2)

Tube Metric	Tube Inch
PP 03C	PP 1/8 C

SPEED CONTROLLERS



Product Code System

METRIC - BSP(R)

NSC 06-01-MO

SPEED CONTROLLERS	TUBE DIA CODE SIZE	THREAD SIZE METRIC THREAD CODE SIZE	CONTROL METHOD METER-OUT CODE No Signal METER-IN CODE IN
04	Ø4	1/8	R
06	Ø6	1/8	R
08	Ø8	1/8	R
10	Ø10	1/8	R
12	Ø12	1/8	R

INCH - BSP(R)

NSC 1/4-01

SPEED CONTROLLERS	TUBE DIA CODE SIZE	THREAD SIZE METRIC THREAD CODE SIZE	CONTROL METHOD METER-OUT CODE No Signal METER-IN CODE IN
1/8	Ø1/8	1/8	R
1/4	Ø1/4	1/8	R
3/8	Ø3/8	1/8	R
1/2	Ø1/2	1/8	R
3/4	Ø3/4	1/8	R

METRIC - BSP(R)

NSC 06-G01

SPEED CONTROLLERS	TUBE DIA CODE SIZE	THREAD SIZE DIPPT THREAD CODE SIZE	CONTROL METHOD METER-OUT CODE No Signal METER-IN CODE IN
04	Ø4	G1/8	G
06	Ø6	G1/8	G
08	Ø8	G1/8	G
10	Ø10	G1/8	G
12	Ø12	G1/8	G

INCH - NPT

NSC 1/4-NI-MO

SPEED CONTROLLERS	TUBE DIA CODE SIZE	THREAD SIZE UNF THREAD CODE SIZE	CONTROL METHOD METER-OUT CODE No Signal METER-IN CODE IN
1/8	Ø1/8	NPT 1/8	R
1/4	Ø1/4	NPT 1/8	R
3/8	Ø3/8	NPT 1/8	R
1/2	Ø1/2	NPT 1/8	R
3/4	Ø3/4	NPT 1/8	R

Uses

- This valve is used to control the speed of pneumatic driving devices.
- Installed mainly in air driving devices

Features

- Flow control is easy for fine control.
- Main body can be rotated 360° after installation.
- Tube direction and angle can be adjusted according to piping.
- Use screw driver to easily adjust speed in narrow and restricted areas. (NSC [D] type)
- Occupies small area when installed.


Specifications

Applicable fluid	compressed air (Not applicable to gases or liquids)
Operating pressure	14.2~150PSI / 1~9.9kgf/cm ² (100~990kPa) ※ The combination with the applied tube shall be decided based on maximum operating pressure of the tube.
Operating temperature range	32~140° F / 0~60° C
Hose materials used	polyurethane, nylon

Structural drawing



Example of use



CAUTIONS

- Note safety precautions, how to classify warning signs (p. 25), and common precautions for fitting products (p. 26) before using.
- Not to be used as a stop valve where there should be no leakage. Allows a certain amount of leakage, so avoid using under conditions that require zero leakage.

WARNINGS

- Check direction of air flow control before using. If used in reverse direction, there is a risk of personal injury as the speed control needle will not work properly, the device may be damaged, and the actuator bounce to go out.
- Adjust speed by fully closing the needle and then slowly opening it.
- Check the number of turns of the needle valve in use. Rotating the needle too many turns may cause damage.
- Do not impact on or forcibly rotate the body or fitting. This may cause product damage or air leakage.

MSC

Elbow
Swivel rotating type

MSC-G

Elbow
Swivel rotating type

MODEL (Φ-D-T)

Tube Metric - Thread R		Tube Inch-Thread R	Tube Inch-Thread NPT	Tube Metric - Thread G	
MSC 03-M5	MSC 06-02	NSC 1/4-M5	NSC 1/4-U	NSC 1/4-N03	MSC 04-G01
MSC 04-M3	MSC 06-02	NSC 1/4-M3	NSC 1/4-U	NSC 1/4-N01	MSC 10-G01
MSC 04-M5	MSC 08-04	NSC 1/2-M5	NSC 1/2-U	NSC 1/2-N02	MSC 06-G01
MSC 04-G01	MSC 06-01	NSC 1/8-G01	NSC 1/8-N02	NSC 1/8-N03	MSC 06-G02
MSC 04-G02	MSC 10-02	NSC 1/8-G02	NSC 1/8-N04	MSC 06-G03	MSC 12-G02
MSC 06-M5	MSC 10-03	NSC 1/8-G03	NSC 1/8-N01	NSC 1/8-N02	MSC 06-G04
MSC 06-G01	MSC 10-04	NSC 1/8-G04	NSC 1/8-N02	MSC 1/8-N03	MSC 12-G04
MSC 08-02	MSC 12-02	NSC 1/8-G05	NSC 1/8-N03	NSC 1/8-N04	MSC 08-G02
MSC 08-G03	MSC 12-03	NSC 1/2-U	NSC 1/2-N02	MSC 08-G03	
MSC 06-G04	MSC 12-04	NSC 1/4-N01	NSC 1/2-N03	MSC 08-G04	
MSC 08-G01		NSC 1/4-N02	NSC 1/2-N04		

NSC(D)

Elbow
Swivel rotating type

NSC-G(D)

Elbow
Swivel rotating type

MODEL (Φ-D-T)

Tube Metric - Thread R		Tube Inch-Thread R	Tube Inch-Thread NPT	Tube Metric - Thread G	
NSC 03-M5(D)	NSC 06-02(D)	NSC 1/4-M5(D)	NSC 1/4-U(D)	NSC 1/4-N03(D)	NSC 04-G01(D)
NSC 04-M3(D)	NSC 06-02(D)	NSC 1/4-M3(D)	NSC 1/4-U(D)	NSC 1/4-N01(D)	NSC 10-G01(D)
NSC 04-G01(D)	NSC 06-04(D)	NSC 1/2-M5(D)	NSC 1/2-U(D)	NSC 1/2-N02(D)	NSC 06-G01(D)
NSC 04-G02(D)	NSC 10-01(D)	NSC 1/8-G01(D)	NSC 1/8-N02(D)	NSC 1/8-N03(D)	NSC 06-G02(D)
NSC 06-M5(D)	NSC 10-02(D)	NSC 1/8-G02(D)	NSC 1/8-N04(D)	NSC 06-G03(D)	NSC 10-G02(D)
NSC 06-G01(D)	NSC 10-03(D)	NSC 1/8-G03(D)	NSC 1/8-N01(D)	NSC 1/8-N02(D)	NSC 06-G04(D)
NSC 06-G02(D)	NSC 10-04(D)	NSC 1/8-G04(D)	NSC 1/8-N02(D)	NSC 1/8-N03(D)	NSC 12-G03(D)
NSC 08-02(D)	NSC 12-02(D)	NSC 1/8-G05(D)	NSC 1/8-N03(D)	NSC 1/8-N04(D)	NSC 08-G02(D)
NSC 08-G03(D)	NSC 12-03(D)	NSC 1/2-U(D)	NSC 1/2-N02(D)	NSC 08-G03(D)	
NSC 06-G04(D)	NSC 12-04(D)	NSC 1/4-N01(D)	NSC 1/2-N03(D)	NSC 08-G04(D)	
NSC 08-G01(D)		NSC 1/4-N02(D)	NSC 1/2-N04(D)		

NSC(DC)

Elbow
Swivel rotating type

NSC-G(DC)

Elbow
Swivel rotating type

MODEL (Φ-D-T)

Tube Metric - Thread R		Tube Inch-Thread R	Tube Inch-Thread NPT	Tube Metric - Thread G	
NSC 03-M5(DC)	NSC 06-03(DC)	NSC 1/4-M5(DC)	NSC 1/4-U(DC)	NSC 1/4-N03(DC)	NSC 04-G02(DC)
NSC 04-M3(DC)	NSC 06-04(DC)	NSC 1/4-M3(DC)	NSC 1/4-U(DC)	NSC 1/4-N01(DC)	NSC 10-G03(DC)
NSC 04-G01(DC)	NSC 08-04(DC)	NSC 1/2-M5(DC)	NSC 1/2-U(DC)	NSC 1/2-N02(DC)	NSC 06-G01(DC)
NSC 04-G02(DC)	NSC 10-02(DC)	NSC 1/8-G01(DC)	NSC 1/8-N02(DC)	NSC 1/8-N03(DC)	NSC 06-G02(DC)
NSC 06-M5(DC)	NSC 10-03(DC)	NSC 1/8-G02(DC)	NSC 1/8-N04(DC)	NSC 06-G03(DC)	NSC 12-G03(DC)
NSC 06-G01(DC)	NSC 10-04(DC)	NSC 1/8-G03(DC)	NSC 1/8-N01(DC)	NSC 1/8-N02(DC)	NSC 06-G04(DC)
NSC 08-02(DC)	NSC 12-02(DC)	NSC 1/8-G04(DC)	NSC 1/8-N02(DC)	NSC 1/8-N03(DC)	NSC 08-G02(DC)
NSC 08-G03(DC)	NSC 12-03(DC)	NSC 1/2-U(DC)	NSC 1/2-N02(DC)	NSC 08-G03(DC)	
NSC 06-G04(DC)	NSC 12-04(DC)	NSC 1/4-N01(DC)	NSC 1/2-N03(DC)	NSC 08-G04(DC)	
NSC 08-G01(DC)		NSC 1/4-N02(DC)	NSC 1/2-N04(DC)		

NSS

Elbow
Swivel rotating type

NSS-G

Elbow
Swivel rotating type

MODEL (Φ-D-T)

Tube Metric - Thread R		Tube Metric - Thread G	Tube Metric - Thread G	
NSS 04-M5	NSS 06-03	NSS 10-03	NSS 04-G01	NSS 08-G02
NSS 04-G01	NSS 08-01	NSS 10-04	NSS 04-G02	NSS 08-G03
NSS 04-G02	NSS 08-02	NSS 12-02	NSS 06-G01	NSS 08-G04
NSS 06-M5	NSS 08-03	NSS 12-03	NSS 06-G02	NSS 10-G02
NSS 06-G01	NSS 08-04	NSS 12-04	NSS 06-G03	NSS 10-G03
NSS 08-02	NSS 10-02		NSS 08-G01	NSS 10-G04

NSS(D)

Elbow
Swivel rotating type

NSS-G(D)

Elbow
Swivel rotating type

MODEL (Φ-D-T)

Tube Metric - Thread R		Tube Metric - Thread G	Tube Metric - Thread G	
NSS 04-M5(D)	NSS 06-03(D)	NSS 10-03(D)	NSS 04-G01(D)	NSS 08-G02(D)
NSS 04-G01(D)	NSS 08-01(D)	NSS 10-04(D)	NSS 04-G02(D)	NSS 08-G03(D)
NSS 04-G02(D)	NSS 08-02(D)	NSS 12-02(D)	NSS 06-G01(D)	NSS 12-G03(D)
NSS 06-M5(D)	NSS 08-03(D)	NSS 12-03(D)	NSS 06-G02(D)	NSS 10-G02(D)
NSS 06-G01(D)	NSS 08-04(D)	NSS 12-04(D)	NSS 06-G03(D)	NSS 10-G03(D)
NSS 08-02(D)	NSS 10-02(D)		NSS 08-G01(D)	NSS 10-G04(D)

NSS(DC)

Elbow
Swivel rotating type

NSS-G(DC)

Elbow
Swivel rotating type

MODEL (Φ-D-T)

Tube Metric - Thread R		Tube Metric - Thread G	Tube Metric - Thread G	
NSS 04-M5(DC)	NSS 06-03(DC)	NSS 10-03(DC)	NSS 04-G01(DC)	NSS 08-G02(DC)
NSS 04-G01(DC)	NSS 08-01(DC)	NSS 10-04(DC)	NSS 04-G02(DC)	NSS 08-G03(DC)
NSS 04-G02(DC)	NSS 08-02(DC)	NSS 12-02(DC)	NSS 06-G01(DC)	NSS 12-G03(DC)
NSS 06-M5(DC)	NSS 08-03(DC)	NSS 12-03(DC)	NSS 06-G02(DC)	NSS 10-G02(DC)
NSS 06-G01(DC)	NSS 08-04(DC)	NSS 12-04(DC)	NSS 06-G03(DC)	NSS 10-G03(DC)
NSS 08-02(DC)	NSS 10-02(DC)		NSS 08-G01(DC)	NSS 10-G04(DC)

NSF



MODEL(ØD)

Tube Metric	Tube Inch
NSF 04	NSF 1/32
NSF 06	NSF 1/16
NSF 08	NSF 1/8
NSF 10	NSF 5/16
NSF 12	NSF 3/8
	NSF 1/2

MSF



MODEL(ØD)

Tube Metric	Tube Inch
MSF 04	
MSF 06	
MSF 08	
MSF 10	
MSF 12	

MEVU



MODEL(7)

Tube Metric
MEVU 04
MEVU 06

MEVS



MODEL(7)

Tube Metric
MEVS 04
MEVS 06



Panel Mount Type Speed Control

Uses and Features

- Union speed control valve of panel mount type
- Convenient to attach and detach using hexagon nuts
- Capable of constant speed control

Structural drawing



NSFB



MSFB



Product model name

MODEL (φD)	
Tube Metric	Tube Inch
NSFB 04	NSFB 1/8
NSFB 06	NSFB 1/4
NSFB 08	NSFB 3/8
NSFB 10	NSFB 1/2
NSFB 12	NSFB 3/4


MODEL (φD)	
Tube Metric	Tube Inch
MSFB 04	MSFB 1/8
MSFB 06	MSFB 1/4
MSFB 08	MSFB 3/8
MSFB 10	MSFB 1/2
MSFB 12	MSFB 3/4

Quick Exhaust Speed Controllers

Uses and Features

- Quick exhaust valve + exhaust speed regulator function
- Capable of high-speed operation of the cylinder
- One-touch fitting with built-in silencer speed control

Structural drawing



ESC



Product model name


MODEL (φD-T)			
Tube Metric - Thread M	Tube Metric - Thread R	Tube Metric - Thread R	Tube Metric - Thread R
ESC 04-M3	ESC 06-S-01	ESC 08-M-01	ESC 10-L-02
ESC 04-M5	ESC 06-S-02	ESC 08-M-02	ESC 10-L-03
ESC 06-M5	ESC 08-S-01	ESC 08-M-03	ESC 10-L-04
	ESC 08-S-02	ESC 10-M-01	ESC 12-L-02
		ESC 10-M-02	ESC 12-L-03
		ESC 10-M-03	ESC 12-L-04

In-Line Speed Controllers with Exhaust Valve

Uses and Features

- Speed control valve of metal body type to be used in piping.
- Compact size for utilizing small areas.

Structural drawing



NSFP



MODEL(T)

Thread R

NSFP 01

NSFP 02

NSFP 03

NSFP 04


Product model name

Speed Controllers with Quick Exhaust Valve

Uses and Features

- Valve used for speed control and residual pressure release.
- Easy in fine flow control.
- Capable of constant speed control.

Structural drawing



NSCP

Elbow
Swivel rotating type



NSCP-G

Elbow
Swivel rotating type



Product model name

MODEL(#D-T)

Tube Metric - Thread R		Tube Metric - Thread G	
NSCP 04-01	NSCP 08-04	NSCP 04-G01	NSCP 08-G04
NSCP 04-02	NSCP 10-01	NSCP 04-G02	NSCP 10-G01
NSCP 06-01	NSCP 10-02	NSCP 06-G01	NSCP 10-G02
NSCP 06-02	NSCP 10-03	NSCP 06-G02	NSCP 10-G03
NSCP 06-03	NSCP 10-04	NSCP 06-G03	NSCP 10-G04
NSCP 06-04	NSCP 12-02	NSCP 06-G04	NSCP 12-G02
NSCP 08-01	NSCP 12-03	NSCP 08-G01	NSCP 12-G03
NSCP 08-02	NSCP 12-04	NSCP 08-G02	NSCP 12-G04
NSCP 08-03		NSCP 08-G03	

NSSP

Elbow
Swivel rotating type



NSSP-G

Elbow
Swivel rotating type



MODEL(#D-T)

Tube Metric - Thread R		Tube Metric - Thread G	
NSSP 04-01	NSSP 08-04	NSSP 04-G01	NSSP 08-G04
NSSP 04-02	NSSP 10-02	NSSP 04-G02	NSSP 10-G02
NSSP 06-01	NSSP 10-03	NSSP 06-G01	NSSP 10-G03
NSSP 06-02	NSSP 10-04	NSSP 06-G02	NSSP 10-G04
NSSP 06-03	NSSP 12-02	NSSP 06-G03	NSSP 12-G02
NSSP 08-01	NSSP 12-03	NSSP 08-G01	NSSP 12-G03
NSSP 08-02	NSSP 12-04	NSSP 08-G02	NSSP 12-G04
NSSP 08-03		NSSP 08-G03	

PILOT CHECK VALVES SPEED CONTROLLERS



Product Code System

METRIC - BSP(T)(R) PVSC 06-01			METRIC - BSP(P)(G) PVSC 06-G01		
SPEED CONTROLLER WITH PILOT CHECK VALVE FITTING	TUBE DIA CODE SIZE	THREAD SIZE	TUBE DIA CODE SIZE	THREAD SIZE CODE SIZE	
	06 Ø6	01 R $\frac{1}{8}$			
	08 Ø8	02 R $\frac{1}{4}$			
	10 Ø10	03 R $\frac{3}{8}$			
	12 Ø12	04 R $\frac{1}{2}$			
BSP(T)(R) PVSF 01			INCH - NPT PVSF - N1		
WITH PILOT CHECK VALVE FITTING	THREAD SIZE CODE SIZE		NPT THREAD CODE SIZE	THREAD SIZE CODE SIZE	
	01 R $\frac{1}{8}$				
	02 R $\frac{1}{4}$				
	03 R $\frac{3}{8}$				
	04 R $\frac{1}{2}$				
BSP(P)(G) PVSF G01			BSP(P)(G) PVSF G01		
	THREAD SIZE CODE SIZE			THREAD SIZE CODE SIZE	
	G01 G $\frac{1}{8}$				
	G02 G $\frac{1}{4}$				
	G03 G $\frac{3}{8}$				
	G04 G $\frac{1}{2}$				

Uses

- This fitting is capable temporary intermediate stop of cylinder.
- Capable of adjusting cylinder speed.


Features

- This product combines the pilot check valve and speed controller as one body.
- Capable of freely setting direction for attaching the tube at any angle.
- Capable of a temporary intermediate stop of the cylinder.
- Possible to prevent sagging due to vertical self-load when air is blocked in OFF mode.

Specifications

Applicable fluid	compressed air (Not applicable to gases or liquids)
Operating pressure	14.2~150PSI / 1~93kgf / (100~900kPa) ※ The combination with the applied tube shall be decided based on the maximum operating pressure of the tube.
Operating temperature range	32~140° F / 0~60° C
Hose materials used	polyurethane, nylon

Structural drawing



Example of Uses

- Use a spanner or a hexagonal wrench when assembling by screw fastening.
- Possible to prevent sagging due to vertical self-load when air is blocked in OFF mode.



PVSC PVSC-G PVSF PVSF-G



Product model name

MODEL (P-Q-T)	
Tube Metric - Thread R	Tube Metric - Thread G
PVSC 06-01	PVSC 06-G01
PVSC 06-02	PVSC 06-G02
PVSC 08-01	PVSC 08-G01
PVSC 08-02	PVSC 08-G02
PVSC 08-03	PVSC 08-G03
PVSC 10-03	PVSC 10-G03
PVSC 10-04	PVSC 10-G04
PVSC 12-03	PVSC 12-G03
PVSC 12-04	PVSC 12-G04

MODEL (T)		
Thread R	Thread NPT	Thread G
PVSF 01	PVSF N01	PVSF G01
PVSF 02	PVSF N02	PVSF G02
PVSF 03	PVSF N03	PVSF G03
PVSF 04	PVSF N04	PVSF G04

HAND VALVES / HAND SLIDE



Product Code System

METRIC - BSPP(R)

HVC 06-01

HAND VALVE	TUBE DIA CODE	TUBE DIA ØD	THREAD SIZE CODE	THREAD SIZE SIZE
	06	Ø6	01	R1/4
	08	Ø8	02	R1/2
	10	Ø10	03	R3/4
	12	Ø12	04	R1

METRIC - BSPP(G)

HVC 06-G01

HAND VALVE	TUBE DIA CODE	TUBE DIA ØD	THREAD SIZE CODE	THREAD SIZE SIZE
	06	Ø6	G01	G1/4
	08	Ø8	G02	G1/2
	10	Ø10	G03	G3/4
	12	Ø12	G04	G1

INCH - NPT

HVC 1/4 -N1

HAND VALVE	TUBE DIA CODE	TUBE DIA ØD	THREAD SIZE CODE	THREAD SIZE SIZE
	1/4	3/8"	N1	NPT 1/4
	1/2	1/2"	N2	NPT 1/2
	3/4	3/4"	N3	NPT 3/4
	1	1"	N4	NPT 1

Uses

- Used to open and close air pressure on the device.


Features

- Turn the handle to open or shut compressed air for the pneumatic devices.
- Repair or inspection can be carried out with residual pressure inside the machine removed.
- When OFF, the 3-way valve releases residual pressure inside the machine into the atmosphere and blocks incoming air as well.
- 4 types depending on how pressured air flow is applied.

Specifications

Applicable fluid	compressed air (NOT applicable to gases or liquids)
Operating pressure	0~150PSI / 0~9.9kgf/cm ² (0~990kPa) ※ The combination with the applied tube shall be decided based on the maximum operating pressure of the tube.
Negative pressure	-29.5 in Hg / -750mmHg(-750Torr)
Operating temperature range	32~140° F / 0~60° C
Hose materials used	polyurethane, nylon

Structural drawing



Example of uses

- When connecting tube, push it into the fitting at the end of the tube. When tube is detached, shut off the compressed air, then gently press down on the sleeve to take the tube out.
- Hand valves discharge residual air in the 3-way method, so employ according to the purpose of use. Applying to other fluids than air may cause leakage.



CAUTIONS

Hand Valves

- Be sure to note safety precautions, how to classify warning signs (p.25), and common precautions for fitting products before using.

WARNINGS

- Do not impact on or forcibly rotate the body or fitting.
- When used in a vacuum, inhaled dust and foreign substances may cause malfunction, so attach a vacuum filter to the suction side.
- When manipulating the hand lever, turn fully to the right or left.
If the hand lever is not fully turned to 90°, flow rate may not be smooth and low due to insufficient switching.

CAUTIONS

Hand Slide Valves

- Be sure to note safety precautions, how to classify warning signs (p.25), and common precautions (p.26) for fitting products before using.
- When manipulating the hand lever, turn fully to the right or left.
If the hand lever is not turned fully right or left, the flow rate is not smooth and low due to insufficient switching.

WARNINGS

- Do not impact on or forcibly rotate the body or fitting. May cause product damage or air leakage.
- Use after identifying air flow control direction.
- Before conducting machine repair and inspection, make sure to shut off the power or air and completely remove residual pressure inside the piping.

HVC

Straight A



MODEL(ΦD-T1)

HVC-G

Straight A



Tube Metric - Thread R		Tube Inch - Thread NPT		Tube Metric - Thread G	
HVC 04-01	HVC 08-03	HVC 1/16"-N01	HVC 1/16"-N03	HVC 04-G01	HVC 08-G03
HVC 04-02	HVC 10-02	HVC 1/8"-N02	HVC 1/8"-N03	HVC 04-G02	HVC 10-G02
HVC 04-03	HVC 10-03	HVC 1/8"-N03	HVC 1/8"-N03	HVC 04-G03	HVC 10-G03
HVC 06-01	HVC 10-04	HVC 1/4"-N01	HVC 1/4"-N04	HVC 06-G01	HVC 10-G04
HVC 06-02	HVC 12-02	HVC 1/4"-N02	HVC 1/4"-N02	HVC 06-G02	HVC 12-G02
HVC 06-03	HVC 12-03	HVC 1/4"-N03	HVC 1/4"-N03	HVC 06-G03	HVC 12-G03
HVC 08-01	HVC 12-04	HVC 1/2"-N01	HVC 1/2"-N04	HVC 08-G01	HVC 12-G04
HVC 08-02		HVC 1/2"-N02		HVC 08-G02	

HVF

Straight B



MODEL(T-ΦD)

HVF-G

Straight B



Thread R - Tube Metric		Thread NPT - Tube Inch		Thread G - Tube Metric	
HVF 01-04	HVF 03-08	HVF N01-1/32	HVF N03-1/16	HVF G01-04	HVF G03-08
HVF 02-04	HVF 02-10	HVF N02-1/32	HVF N02-1/16	HVF G02-04	HVF G02-10
HVF 03-04	HVF 03-10	HVF N03-1/32	HVF N03-1/16	HVF G03-04	HVF G03-10
HVF 01-06	HVF 04-10	HVF N01-1/16	HVF N04-1/8	HVF G01-06	HVF G04-10
HVF 02-06	HVF 02-12	HVF N02-1/16	HVF N02-1/8	HVF G02-06	HVF G02-12
HVF 03-06	HVF 03-12	HVF N03-1/16	HVF N03-1/8	HVF G03-06	HVF G03-12
HVF 01-08	HVF 04-12	HVF N01-1/8	HVF N04-1/4	HVF G01-08	HVF G04-12
HVF 02-08		HVF N02-1/8		HVF G02-08	

HVU

Union Straight



MODEL(ΦD1-ΦD2)

Tube Metric	Tube Inch
HVU 04-04	HVU 1/16"-1/16"
HVU 06-06	HVU 1/8"-1/8"
HVU 08-06	HVU 1/16"-1/4"
HVU 08-08	HVU 1/16"-1/8"
HVU 10-08	HVU 1/8"-1/8"
HVU 10-10	HVU 1/8"-1/4"
HVU 12-10	HVU 1/2"-1/8"
HVU 12-12	HVU 1/2"-1/2"

HSV

Nipple Slide



MODEL(T)

Thread R
HSV M5
HSV 01
HSV 02
HSV 03
HSV 04
HSV 06

HVM

Nipple



MODEL(T1-T2)

Thread R	Thread NPT	Thread G
HVM 01-01	HVM N01-N01	HVM G01-G01
HVM 02-01	HVM N02-N01	HVM G02-G01
HVM 02-02	HVM N02-N02	HVM G02-G02
HVM 03-02	HVM N03-N02	HVM G03-G02
HVM 03-03	HVM N03-N03	HVM G03-G03
HVM 04-03	HVM N04-N03	HVM G04-G03
HVM 04-04	HVM N04-N04	HVM G04-G04

HVM-G

Nipple



HBVU 0606

TUBE DIA	
CODE	SIZE
06	Ø6
08	Ø8
10	Ø10
12	Ø12

CD PNEUMATICS 67

STOP FITTINGS



Product Code System

METRIC - BSP^(R)

SPC 06-01

STOP FITTING	TUBE DIA CODE Ø" D	THREAD SIZE CODE SIZE
04	Ø4	M5 M5×0.8
06	Ø6	M6 M6×1.0
08	Ø8	01 R½
10	Ø10	02 R½
12	Ø12	03 R½
		04 R½

METRIC - BSP^(G)

SPC 06-G01

STOP FITTING	TUBE DIA CODE Ø" D	THREAD SIZE CODE SIZE
04	Ø4	G01 G½
06	Ø6	G02 G½
08	Ø8	G03 G½
10	Ø10	G04 G½
12	Ø12	

INCH - NPT

SPC 1/4-N1

STOP FITTING	TUBE DIA CODE Ø" D	THREAD SIZE CODE SIZE
1/8	Ø 1/8	U 10-32UNF
1/4	Ø 1/4	N1 NPT 1/4
3/8	Ø 3/8	N2 NPT 1/2
1/2	Ø 1/2	N3 NPT 3/4
3/4	Ø 3/4	N4 NPT 1

Uses

- Used often where pneumatic piping is changed frequently

Features

- When the tube is removed, the air is completely blocked. When connected again, the air is to flow for the purpose of ensuring good maintenance or safety of the device.
- With the stop fitting installed, compressed air is supplied only when the tube is connected


Specifications

Applicable fluid	compressed air (Not applicable to gases or liquids)
Operating pressure	0~150PSI / 0~9.8kgf/cm ² ~99kPa ※ The combination with the applied tube shall be decided based on the maximum operating pressure of the tube.
Negative pressure	-29.5 in Hg / -750mmHg/-750Torr
Operating temperature range	32~140° F / 0~60° C
Hose materials used	polyurethane, nylon

Structural drawing



Example of uses



CAUTIONS

- Be sure to note safety precautions, the classification method of warning signs (p.25), and the common precautions for fitting products (p.24) before using them.
- Assemble with reference to proper fastening torque for fitting. (p.26)
- Fasten by hand and rotate 2-3 turns with a tool. Be careful that fastening too hard may damage the screw thread.
- When the tube is installed, check the direction of the air flow before using it.
- If assembled in the opposite direction to air flow, air does not flow. Check the direction of air flow before piping and assembling

WARNINGS

- Do not impact on or forcibly rotate the body or fitting.
- Do not open the tube with pressure applied when opening the tube. The bouncing force of the tube under pressure can cause damage to the human body. Please be careful when using it.

SPC

Straight



SPC-G

Straight



MODEL(φD-T)

Tube Metric -Thread R		Tube Inch -Thread NPT		Tube Metric -Thread G	
SPC 04-G1	SPC 10-G3	SPC 1/8-N01	SPC 1/8-N03	SPC 04-G01	SPC 10-G03
SPC 06-G1	SPC 10-G4	SPC 1/8-N01	SPC 1/8-N02	SPC 06-G01	SPC 10-G04
SPC 06-G2	SPC 12-G2	SPC 1/8-N02	SPC 1/8-N03	SPC 06-G02	SPC 12-G02
SPC 08-G2	SPC 12-G3	SPC 1/8-N01	SPC 1/8-N04	SPC 08-G02	SPC 12-G03
SPC 08-G3	SPC 12-G4	SPC 1/8-N02	SPC 1/8-N03	SPC 08-G03	SPC 12-G04
SPC 10-G2		SPC 1/8-N01	SPC 1/8-N04	SPC 10-G02	
		SPC 1/8-N02			

SPL

Elbow



SPL-G

Elbow



MODEL(φD-T)

Tube Metric -Thread R		Tube Inch -Thread NPT		Tube Metric -Thread G	
SPL 04-M5	SPL 08-G2	SPL 1/8-U	SPL 1/8-N01	SPL 04-G01	SPL 10-G04
SPL 04-M6	SPL 08-G3	SPL 1/8-U	SPL 1/8-N02	SPL 06-G01	SPL 12-G03
SPL 04-G1	SPL 10-G2	SPL 1/8-U	SPL 1/8-N03	SPL 06-G02	SPL 12-G04
SPL 06-M5	SPL 10-G3	SPL 1/8-N01	SPL 1/8-N02	SPL 08-G02	
SPL 06-G1	SPL 10-G4	SPL 1/8-N02	SPL 1/8-N03	SPL 08-G03	
SPL 06-G2	SPL 12-G3	SPL 1/4-U	SPL 1/4-N04	SPL 10-G02	
SPL 08-G1	SPL 12-G4	SPL 1/4-N01	SPL 1/4-N03	SPL 10-G03	
		SPL 1/4-N02	SPL 1/4-N04		

SPU

Union Straight



SPUM



MODEL(φD)

Tube Metric	Tube Inch
SPU 04	SPU 1/8
SPU 06	SPU 1/4
SPU 08	SPU 1/2
SPU 10	SPU 3/4
SPU 12	SPU 1

MODEL(φD)

Tube Metric	Tube Inch
SPUM 04	
SPUM 06	
SPUM 08	
SPUM 10	
SPUM 12	



CHECK VALVES



Product Code System

METRIC - (SUPT)R

CVPC 08-01-MO

CHECK VALVES	TUBE DIA	THREAD SIZE	CONTROL METHOD
CODE I #0	CODE I SIZE	CODE I SIZE	METER-OUT
04	04	M5	OUT
06	06	G1	IN
08	08	G1/2	IN
10	10	G3/4	IN
12	12	G1	IN

METRIC - (SUPT)B

CVPC 08-G01-MO

CHECK VALVES	TUBE DIA	THREAD SIZE	CONTROL METHOD
CODE I #0	CODE I SIZE	CODE I SIZE	METER-OUT
04	04	G1/1	OUT
06	06	G1/2	OUT
08	08	G3/4	OUT
10	10	G1	OUT
12	12	G1 1/4	OUT

INCH - NPT

CVPC 5/16-N1-MO

CHECK VALVES	TUBE DIA	THREAD SIZE	CONTROL METHOD
CODE I #0	CODE I SIZE	CODE I SIZE	METER-OUT
1/8	1/8"	1/16 NPT	OUT
1/4	1/4"	1/8 NPT	OUT
3/8	3/8"	1/4 NPT	OUT
1/2	1/2"	1/2 NPT	OUT

Uses

- Used where air flow passes only in one direction.
- Used where the air pressure is required to remain constant on the exhaust side.
- Suitable for piping the devices used under low pressure

Features

- Easily used in environments where the vacuum line is protected and maintained, and under low pressure conditions by allowing compressed air entered in one direction to flow and by blocking air flow in the opposite direction.
- Female screw threads in both directions and metal body type (CVFF)


Specifications

Applicable fluid	compressed air (Not applicable to gases or liquids)
Operating pressure	150PSI / 9.8kgf/cm ² (990kPa) * The combination with the applied tube shall be decided based on the maximum operating pressure of the tube.
Cracking pressure	0.1 ~ 0.2kgf/cm ²
Negative pressure	-29.5 in Hg / -750mmHg (-750Torr)
Operating temperature range	32 ~ 140° F / 0 ~ 60° C
Hose materials used	polyurethane, nylon

Structural drawing



Example of uses



CAUTIONS

- Be sure to note the safety precautions, the classification method of warning signs (p. 25), and the common precautions for fitting products before using them.
- Assemble with reference to proper fastening torque for fitting. (p.26)
- Fasten by hand and rotate 2-3 turns with a tool. Fastening too hard may cause operating failure of the valve.

WARNINGS

- Do not impact on or forcibly rotate the body or fitting.
- Note that heat may be generated in the valve due to switching operation at a high frequency. Please be careful to avoid burns due to the heat.

CVPC

Straight



CVPC-G

Straight



MODEL(φD-T)

Tube Metric - Thread R	Tube Inch - Thread NPT	Tube Metric - Thread G
CVPC 04-M5	CVPC 1/8-U	CVPC 04-G01
CVPC 04-M5	CVPC 1/8-N01	CVPC 06-G01
CVPC 04-M5	CVPC 1/8-N02	CVPC 06-G02
CVPC 04-M5	CVPC 1/8-N03	CVPC 06-G01
CVPC 04-M5	CVPC 1/8-N04	CVPC 06-G02
CVPC 06-M6	CVPC 1/2-N01	CVPC 08-G03
CVPC 06-M6	CVPC 1/2-N02	CVPC 08-G04
CVPC 06-M6	CVPC 1/2-N03	CVPC 10-G03
CVPC 06-M6	CVPC 1/2-N04	CVPC 10-G04

※ The large steel Ø 10, Ø 12, Ø 3/8, Ø 1/2 is aluminum body

CVPF

Bush



CVPF-G

Bush



MODEL(T1-T2)

Thread R - Thread Rc	Thread NPT - Thread NPT	Thread G - Thread G
CVPF 01-01	CVPF N01-N01	CVPF G01-G01
CVPF 02-02	CVPF N02-N02	CVPF G02-G02
CVPF 03-03	CVPF N03-N03	CVPF G03-G03
CVPF 04-04	CVPF N04-N04	CVPF G04-G04

CVPU

Union Straight



Metal Body



MODEL(φD)

Tube Metric	Tube Inch
CVPU 04	CVPU 1/8
CVPU 06	CVPU 1/8
CVPU 08	CVPU 1/8
CVPU 10	CVPU 1/8
CVPU 12	CVPU 1/8

CVFF

Union Straight



CVFF-G



MODEL(φD)

Thread Rc - Thread Rc	Thread G - Thread G
CVFF 01-01	CVFF G01-G01
CVFF 02-02	CVFF G02-G02
CVFF 03-03	CVFF G03-G03
CVFF 04-04	CVFF G04-G04



STAINLESS STEEL PUSH-IN FITTINGS



Product Code System

METRIC - BSPF(R)

SUS-PC 04 M5

STAINLESS STEEL PUSH-IN FITTINGS		TUBE DIA CODE SIZE		THREAD SIZE CODE SIZE	
04	Ø4	01	M5	M5	M5×0.8
06	Ø6	01	R1/8		
08	Ø8	02	R1/4		
10	Ø10	03	R3/8		
12	Ø12	04	R1/2		

METRIC - BSPF(G)

SUS-PC 04 -G01

STAINLESS STEEL PUSH-IN FITTINGS		TUBE DIA CODE SIZE		THREAD SIZE GIPF THREAD CODE SIZE	
04	Ø4	001	G 1/8		
06	Ø6	002	G 1/4		
10	Ø10	003	G 3/8		
12	Ø12	004	G 1/2		

Uses

- This pipe connector can be used in special industrial environments, such as those including food and beverages, oil, gas, and chemicals.
- This product is made of materials suitable for use in making chemical and pharmaceutical industry equipment.

Features

- Suitable for environments requiring high temperature and corrosion resistance.
- One-touch manipulating enables to easy attachment and detachment of the tube.


Specifications

Materials	Stainless steel SUS316L
Operating fluids	Air, Oil, air, oil, water, steam
Operating pressure	0~18kgf/cm ²
Operating temperature range	-20~150℃

Structural drawing



Example of uses



CAUTIONS

- Assemble tube after completely removing foreign substances such as dust.
- When using fitting products, ensure beforehand that the outside diameter of the tube falls within the allowable range of the tolerance table.

WARNINGS

- Do not use it for fluids other than air. For use with other fluids or gases, contact CDC Pneumatic Technical Department.
- Be careful of pressure increases due to twisting, pulling, bending, etc.
- Do not use in places with welding flames.
- Not available due to rapid rotation and vibration that may cause product damage and air leakage, please refer to our catalog to select the correct product.
- Do not use cutting oil, lubricant, coolant, etc. in direct contact with the solution.

SUS-PC



MODEL(φD-T)

Tube Metric -Thread R		Tube Metric -Thread G	
SUS-PC 04M5	SUS-PC 0603	SUS-PC 04G01	SUS-PC 10G02
SUS-PC 0601	SUS-PC 1002	SUS-PC 06G02	SUS-PC 12G03
SUS-PC 0402	SUS-PC 1003	SUS-PC 06G01	SUS-PC 12G02
SUS-PC 06M5	SUS-PC 1202	SUS-PC 06G02	SUS-PC 12G03
SUS-PC 0601	SUS-PC 1203	SUS-PC 06G01	SUS-PC 12G04
SUS-PC 0602	SUS-PC 1204	SUS-PC 06G02	
SUS-PC 0601		SUS-PC 06G03	
SUS-PC 0602			

SUS-PC-G



SUS-PUL



MODEL(φD)

Tube Metric -Thread R	
SUS-PUL 04	
SUS-PUL 06	
SUS-PUL 08	
SUS-PUL 10	
SUS-PUL 12	

SUS-PL



MODEL(φD-T)

Tube Metric -Thread R		Tube Metric -Thread G	
SUS-PL 04M5	SUS-PL 0603	SUS-PL 04G01	SUS-PL 10G02
SUS-PL 0401	SUS-PL 1002	SUS-PL 04G02	SUS-PL 12G03
SUS-PL 0402	SUS-PL 1003	SUS-PL 06G01	SUS-PL 12G02
SUS-PL 06M5	SUS-PL 1202	SUS-PL 06G02	SUS-PL 12G03
SUS-PL 0601	SUS-PL 1203	SUS-PL 06G01	SUS-PL 12G04
SUS-PL 0602	SUS-PL 1204	SUS-PL 06G02	
SUS-PL 0601		SUS-PL 06G03	
SUS-PL 0602			

SUS-PL-G



SUS-PUT



MODEL(φD)

Tube Metric -Thread R	
SUS-PUT 04	
SUS-PUT 06	
SUS-PUT 08	
SUS-PUT 10	
SUS-PUT 12	

SUS-PUC



MODEL(φD)

Tube Metric -Thread R	
SUS-PUC 04	
SUS-PUC 06	
SUS-PUC 08	
SUS-PUC 10	
SUS-PUC 12	

FITTINGS FOR SECONDARY BATTERY INDUSTRY



Product Code System

METRIC - BSP(PT)

SMPC 06-01

STAINLESS		FITTINGS FOR SECONDARY BATTERY INDUSTRY		TUBE DIA. CODE SIZE	THREAD SIZE CODE SIZE
04	04	M8	M8	M8	M8
06	06	M10	M10	M10	M10
08	08	M12	M12	M12	M12
10	10	M14	M14	M14	M14
12	12	M16	M16	M16	M16
14	14	M20	M20	M20	M20
16	16	M22	M22	M22	M22
		RPT1 THREAD		CODE	SIZE
				01	R1/8
				02	R1/4
				03	R3/8
				04	R1/2

METRIC - BSP(PT)

SMPC 06-G01

STAINLESS		FITTINGS FOR SECONDARY BATTERY INDUSTRY		TUBE DIA. CODE SIZE	THREAD SIZE CODE SIZE
04	04	M8	M8	M8	M8
06	06	M10	M10	M10	M10
08	08	M12	M12	M12	M12
10	10	M14	M14	M14	M14
12	12	M16	M16	M16	M16
14	14	M20	M20	M20	M20
16	16	M22	M22	M22	M22

Uses

- This fitting is applicable for secondary battery industry and its environment.


Features

- Easy to install and remove the tubes by pushing them in with one movement
- Screw threads are O-ringed and Teflon-treated.
- Applicable for up to 20 bar.
- Applicable for up to 80°C.
- The compact design makes it easy to mount in a small area.

Specifications

Operating fluids	compressed air (not applicable to gases or liquids)
Operating pressure	20Bar
Negative pressure	-29.5 in Hg / -750mmHg(-750Torr)
Operating temperature range	-20~80°C
Hose materials used	polyurethane, nylon

Structural drawing



Example of uses

- When assembling by screw fastening, use a spanner or a hexagon wrench to assemble the external or internal hexagon.
- PL and PT models can be used by setting the direction according to the piping. Injection-molded body rotates.
- Sieve is circular and will not interfere with the equipment.



CAUTIONS

- Be sure to note the safety precautions, how to classify the warning signs (p.25), and the precautions for fitting products before using them.
- Assemble by referring to the proper fastening torque for fittings. (p.26)
- The standard is to tighten by hand and then rotate 2 to 3 turns with the tool. Fastening too hard may damage the screw threads.
- When installing the tube of the fitting, make sure that the tube does not fall out by gently pulling it after cutting at right angles and inserting it inside.
- Avoid piping under tension, and avoid drastically curved piping at the tube inserting inlet of the fitting.

WARNINGS

- Avoid twisting or hitting of the body or the fitting by the impact tool. May cause product damage or air leakage.
- Refrain from using water as the operating fluid if it does not meet all the conditions described in the specifications. May cause breakage of fitting, tube to fall out, and leakage of compressed air.

SMPC



MODEL(ΦD-T)

Tube Metric - Thread R		Tube Metric - Thread G	
SMPC 04-M5	SMPC 08-02	SMPC 04-G01	SMPC 08-G04
SMPC 04-01	SMPC 08-03	SMPC 04-G02	SMPC 10-G02
SMPC 04-02	SMPC 10-02	SMPC 06-G01	SMPC 10-G03
SMPC 06-M5	SMPC 10-03	SMPC 06-G02	SMPC 10-G04
SMPC 06-01	SMPC 10-04	SMPC 06-G03	SMPC 12-G02
SMPC 06-02	SMPC 12-03	SMPC 08-G01	SMPC 12-G03
SMPC 06-01	SMPC 12-04	SMPC 08-G02	SMPC 12-G04
		SMPC 08-G03	

SMPC-G



Speed Controllers

SMSC



MODEL(ΦD-T)

Tube Metric - Thread R		Tube Metric - Thread G	
SMSC 04-M5	SMSC 08-03	SMSC 04-G01	SMSC 08-G04
SMSC 04-01	SMSC 08-04	SMSC 04-G02	SMSC 10-G02
SMSC 04-02	SMSC 10-01	SMSC 06-G01	SMSC 10-G03
SMSC 06-M5	SMSC 10-02	SMSC 06-G02	SMSC 10-G04
SMSC 06-01	SMSC 10-03	SMSC 06-G03	SMSC 12-G02
SMSC 06-02	SMSC 10-04	SMSC 08-G01	SMSC 12-G03
SMSC 06-03	SMSC 12-02	SMSC 08-G02	SMSC 12-G04
SMSC 06-04	SMSC 12-03	SMSC 08-G03	
SMSC 08-01	SMSC 12-04		
SMSC 08-02			

SMSC-G



SMPL



MODEL(ΦD-T)

Tube Metric - Thread R		Tube Metric - Thread G	
SMPL 04-M5	SMPL 08-03	SMPL 04-G01	SMPL 08-G04
SMPL 04-01	SMPL 10-02	SMPL 04-G02	SMPL 10-G02
SMPL 04-02	SMPL 10-03	SMPL 06-G01	SMPL 10-G03
SMPL 06-M5	SMPL 10-04	SMPL 06-G02	SMPL 10-G04
SMPL 06-01	SMPL 12-03	SMPL 06-G03	SMPL 12-G02
SMPL 06-02	SMPL 12-04	SMPL 08-G01	SMPL 12-G03
SMPL 08-01		SMPL 08-G02	SMPL 12-G04
SMPL 08-02		SMPL 08-G03	

SMPL-G



SMSF



MODEL(ΦD)

Tube Metric	Tube Inch
SMSF 04	
SMSF 06	
SMSF 08	
SMSF 10	
SMSF 12	

SMPT



MODEL(ΦD-T)

Tube Metric - Thread R		Tube Metric - Thread G	
SMPT 04-M5	SMPT 08-02	SMPT 04G01	SMPT 08G03
SMPT 04-01	SMPT 08-03	SMPT 04G02	SMPT 08G04
SMPT 04-02	SMPT 10-02	SMPT 04G03	SMPT 10G02
SMPT 06-M5	SMPT 10-03	SMPT 06G01	SMPT 10G03
SMPT 06-01	SMPT 10-04	SMPT 06G02	SMPT 10G04
SMPT 06-02	SMPT 12-03	SMPT 06G03	SMPT 12G02
SMPT 08-01	SMPT 12-04	SMPT 08G01	SMPT 12G03
		SMPT 08G02	SMPT 12G04

SMPT-G



BRASS PUSH-IN FITTINGS



Product Code System

METRIC - BSP(R)

BPC 06-01

BRASS PUSH-IN FITTINGS	TUBE DIA		THREAD SIZE	
	CODE	SIZE	CODE	SIZE
	04	Ø4	01	R1/4
	06	Ø6	02	R1/2
	08	Ø8	03	R3/4
	10	Ø10	04	R1
	12	Ø12		

METRIC - BSP(F)

BPC 06-G01

BRASS PUSH-IN FITTINGS	TUBE DIA		THREAD SIZE	
	CODE	SIZE	CODE	SIZE
	04	Ø4	G01	G1/4
	06	Ø6	G02	G1/2
	08	Ø8	G03	G3/4
	10	Ø10	G04	G1
	12	Ø12		

INCH - NPT

BPC-1/4-N1

BRASS PUSH-IN FITTINGS	TUBE DIA		THREAD SIZE	
	CODE	SIZE	CODE	SIZE
	1/4	Ø1/4	N1	NPT 1/4
	1/2	Ø1/2	N2	NPT 1/2
	3/4	Ø3/4	N3	NPT 3/4
	1	Ø1	N4	NPT 1

Uses

- This is a one-touch type pipe connector to be used for pneumatic piping.


Features

- Easily applicable as a high-specification fitting.
- A compact type that can be mounted in a small space.
- Possible to use a variety of tubes according to use circumstances.


Specifications

Operating pressure	applicable to 0 to 16 Bar.
Operating temperature range	-20°C to +80°C
Material of tube used	PU, PA

Structural drawing



Example of uses



CAUTIONS

- Assemble the tube after removing foreign substances such as dust.
- When using fitting products, ensure beforehand that the outside diameter of the tube falls within the allowable range of the tolerance table.

WARNINGS

- Do not use for fluids other than air. When using for other fluids or gases, please contact CDC Pneumatic Technical Department.
- Be careful of pressure increases due to twisting, pulling, bending, etc.
- Do not use in places with welding flames present.
- Not applicable where rapid rotation and vibration may cause product damage and air leakage. Please refer to our catalog to select the correct product.
- Do not use in environments where cutting oil, lubricant, coolant, etc. may come in direct contact.

BPC
Male Connector**BPC-G**
Male Connector

MODEL(ΦD-T)

Tube Metric - Thread R		Tube Inch - Thread NPT		Tube Metric - Thread G	
BPC 04-R01	BPC 10-R02	BPC 1/8-U	BPC 1/8-N03	BPC 04-M5	BPC 08-G03
BPC 04-R02	BPC 10-R03	BPC 1/8-N01	BPC 1/8-N01	BPC 04-G01	BPC 10-G02
BPC 06-R01	BPC 10-R04	BPC 1/8-N02	BPC 1/8-N02	BPC 04-G02	BPC 10-G03
BPC 06-R02	BPC 12-R02	BPC 1/4-U	BPC 1/4-N03	BPC 06-M5	BPC 10-G04
BPC 08-R01	BPC 12-R03	BPC 1/4-N01	BPC 1/4-N04	BPC 06-G01	BPC 12-G02
BPC 08-R02	BPC 12-R04	BPC 1/4-N02	BPC 1/2-N02	BPC 06-G02	BPC 12-G03
BPC 08-R03		BPC 1/8-N01	BPC 1/2-N03	BPC 08-G01	BPC 12-G04
		BPC 1/8-N02	BPC 1/2-N04	BPC 08-G02	

BPL
Male Elbow**BPL-G**
Male Elbow

MODEL(ΦD-T)

Tube Metric - Thread R		Tube Inch - Thread NPT		Tube Metric - Thread G	
BPL 04-R01	BPL 10-R02	BPL 1/8-U	BPL 1/8-N01	BPL 04-M5	BPL 08-G03
BPL 04-R02	BPL 10-R03	BPL 1/8-N01	BPL 1/8-N02	BPL 04-G01	BPL 10-G02
BPL 06-R01	BPL 10-R04	BPL 1/8-N02	BPL 1/8-N03	BPL 04-G02	BPL 10-G03
BPL 06-R02	BPL 12-R02	BPL 1/4-N01	BPL 1/4-N04	BPL 06-M5	BPL 10-G04
BPL 08-R01	BPL 12-R03	BPL 1/4-N02	BPL 1/2-N02	BPL 06-G01	BPL 12-G02
BPL 08-R02	BPL 12-R04	BPL 1/4-N01	BPL 1/2-N03	BPL 06-G02	BPL 12-G03
BPL 08-R03		BPL 1/8-N01	BPL 1/2-N04	BPL 08-G01	BPL 12-G04
		BPL 1/8-N02		BPL 08-G02	

BPT
Male Branch Tee**BPT-G**
Male Branch Tee

MODEL(ΦD-T)

Tube Metric - Thread R		Tube Inch - Thread NPT		Tube Metric - Thread G	
BPT 04-R01	BPT 10-R02	BPT 1/8-N01	BPT 1/8-N02	BPT 04-M5	BPT 08-G03
BPT 04-R02	BPT 10-R03	BPT 1/8-N02	BPT 1/8-N03	BPT 04-G01	BPT 10-G02
BPT 06-R01	BPT 10-R04	BPT 1/8-N01	BPT 1/8-N02	BPT 04-G02	BPT 10-G03
BPT 06-R02	BPT 12-R02	BPT 1/4-N02	BPT 1/4-N03	BPT 06-M5	BPT 10-G04
BPT 08-R01	BPT 12-R03	BPT 1/4-N01		BPT 06-G01	BPT 12-G02
BPT 08-R02	BPT 12-R04	BPT 1/8-N02		BPT 06-G02	BPT 12-G03
BPT 08-R03				BPT 08-G01	BPT 12-G04
				BPT 08-G02	

BUC
Union Connector

MODEL(ΦD1-ΦD2)

Tube Metric	Tube Inch
BUC 04	BUC 1/4-1/4
BUC 06	BUC 1/8-1/8
BUC 08	BUC 1/2-1/2
BUC 10	
BUC 12	

BUL
Union Elbow

MODEL(ΦD1-ΦD2)

Tube Metric	Tube Inch
BUL 04	BUL 1/4-1/4
BUL 06	BUL 1/8-1/8
BUL 08	BUL 1/2-1/2
BUL 10	
BUL 12	

BUT
Union Tee

MODEL(ΦD1-ΦD2)

Tube Metric	Tube Inch
BUT 04	BUT 1/4-1/4
BUT 06	BUT 1/8-1/8
BUT 08	BUT 1/2-1/2
BUT 10	
BUT 12	

TWO-TOUCH FITTINGS



Product Code System

METRIC - BSPT(R)					
CK 06-01					
TWO TOUCH FITTING	TUBE DIA		THREAD SIZE		
	CODE	O.D	LD	CODE	SIZE
	04	Ø4	Ø2.5	01	R 1/8
	06	Ø6	Ø4	02	R 1/4
	08	Ø8	Ø5.5	03	R 3/8
	10	Ø10	Ø6.5	04	R 1/2
	12	Ø12	Ø8		

Uses

- Nut tightening type pipe connector for pneumatic piping of devices.


Features

- Fastening of the tube is made by nut tightening. Effective where vibration is severe.
- Made of plastic materials with a semi-permanent life span and excellent corrosion and chemical resistance.
- Suitable for use in low-pressure pneumatic applications.


Specifications

Applicable fluid	compressed air (Not applicable to gases or liquids)
Operating pressure	0~150PSI / 0~9.9kgf/cm ² (0~990kPa) ※ The combination with the applied tube shall be decided based on the maximum operating pressure of the tube.
Negative pressure	-25.5 in Hg / -750mmHg(-750cm)
Operating temperature range	32~140° F / 0~60° C
Hose materials used	polyurethane, nylon

Structural drawing



Example of uses



CAUTIONS

- Be sure to note the safety precautions, the classification method of warning signs (p.25), and common precautions of fitting products (p.26) before using them.
- As the material is plastic, Teflon coating is not applied on the screw thread. Applying the Teflon tape before installing will be effective in preventing air leakage.
- Make sure that pulling, bending, or twisting is not applied to the product. Otherwise, damage to the body and/or air leakage may occur.
- When assembling tube, push to the end and tighten the cap completely before using it.

WARNINGS

- When reusing a removed tube, cut the pressed part of the tube off at the right angle and assemble it.
- Product made of plastic so forced fastening may cause damage to the body. Please be careful when assembling.

CK
Straight



MODEL(ØD-T)

Tube Metric - Thread R	
CK 04-01	CK 10-02
CK 06-01	CK 10-03
CK 06-02	CK 12-02
CK 06-03	CK 12-03
CK 08-02	CK 12-04
CK 08-03	

GCK
Elbow



MODEL(ØD-T)

Tube Metric - Thread R	
GCK 04-01	GCK 10-02
GCK 06-01	GCK 10-03
GCK 06-02	GCK 12-02
GCK 06-03	GCK 12-03
GCK 08-02	GCK 12-04
GCK 08-03	

FCK
Union Tee



MODEL(ØD)

Tube Metric	
	FCK 04
	FCK 06
	FCK 08
	FCK 10
	FCK 12



SILENCERS / METAL SILENCERS

Product Code System

ST 01

SILENCER

THREAD SIZE(T) R(P/T) THREAD	
Code	Size
01	R 1/8
02	R 1/4
03	R 1/2
04	R 3/4
05	R 1
06	R 1 1/2

STB 01

METAL SILENCER

THREAD SIZE(T) R(P/T) THREAD	
Code	Size
M5	M5 x 0.8
01	R 1/8
02	R 1/4
03	R 1/2
04	R 3/4
05	R 1
06	R 1 1/2

Uses

- Installed in the exhaust port of the equipment, it is used to reduce the noise of air exhaust.


Features

- Made of corrosion-resistant plastic, has a long-life and light-weight.
- Low unit price and high durability.
- Attached to a pneumatic exhaust, it provides excellent noise silencing effect during exhaust.
- Compact, easy to install in a narrow place.

Specifications


Code	ST01	ST02	ST03	ST04	ST06	ST08
Max. operating pressure	7kgf/cm ² (700kPa)/100PSI			9.9kgf/cm ² (990kPa)/150PSI		

Structural drawing



Example of uses

- When assembling by screw fastening, use a spanner on the hexagonal head.
- If the element is clogged, exhaust resistance increases and the product may be damaged or its performance degraded. Replace when necessary with a new product.



CAUTIONS

- Be sure to note the safety precautions, the classification method of warning signs (p.25), and common precautions of fitting products before using them.
- If the element has become clogged by dust and foreign substances when used for a long time, exhaust resistance may increase. This may adversely affect system performance, including silencing. Replace periodically to prevent from occurring.
- Material is plastic so Teflon coating not applied on the screw thread. Applying Teflon tape before installing will be effective in preventing air leakage.

WARNINGS

- Made of plastic, so forced fastening of the screw may damage the body. Please be careful in assembling.
- Please replace product periodically to prevent damage to the device.

Product model name

ST	MODEL(T)
	Thread R
	ST-01
	ST-02
	ST-03
	ST-04
	ST-06
	ST-08
	STM-02
	STM-03

Metal Silencer

Uses

- Metal filter can be used even at high temperatures and high pressures. Resistant to impact.
- Product used throughout the industry because it is easy to connect, including welding.

Features

- Excellent in noise reduction and filtering under dry conditions.

Specifications

	STB(M5)	STB(M)	STB(M2)	STB(M3)	STB(M4)	STB(M6)	STB(M8)
Max. operating pressure	15kgf/cm ² (220PSI)						
Operating temperature range	0~80℃(32~176°F)						
Flow rate	250	300	320	340	370	400	420

CAUTIONS

- Be sure to note the safety precautions, the classification method of warning signs (p.25), and common precautions of fitting products before using them.
- If the element has become clogged by dust and foreign substances when used for a long time, exhaust resistance may increase. This may adversely affect system performance, including silencing. Replace periodically to prevent from occurring.
- Material is plastic so Teflon coating not applied on the screw thread. Applying Teflon tape before installing will be effective in preventing air leakage.

WARNINGS

- Made of plastic, so forced fastening of the screw may damage the body. Please be careful in assembling.
- Please replace product periodically to prevent damage to the device.

STB



T

MODEL(T)

Thread R		
STB(B)-M5		STB(V)-M5
STB(B)-01		STB(V)-01
STB(B)-02		STB(V)-02
STB(B)-03		STB(V)-03
STB(B)-04		STB(V)-04
STB(B)-06		STB(V)-06
STB(B)-08		STB(V)-08

STB(V)



T

STC



MODEL(T)

Thread R	
STC-01	
STC-02	
STC-03	
STC-04	

Product
model name




POLYURETHANE TUBE / POLYETHYLENE TUBE / NYLON TUBE / COIL TUBE



Company that dreams of Affluent Tomorrow and Technology
that considers the Environment and the Future - CDC Pneumatic

TUBES



Product Code System

POLYURETHANE TUBE		
PU 08 50 BK		
POLYURETHANE TUBE	TUBE DIA (O.D. & I.D.)	TUBE COLOR
METRIC TUBE	INCH TUBE	COLOR CODE
0054E (0.21" ID)	0050E (0.20" ID)	White WT
0330 (0.3" ID)	0300 (0.25" ID)	Black BK
0400 (0.4" ID)	0350 (0.3" ID)	Red RD
0400 (0.4" ID)	0400 (0.4" ID)	Blue BU
0640 (0.6" ID)	0600 (0.5" ID)	Yellow YL
0900 (0.9" ID)	0850 (0.75" ID)	Green GR
0900 (0.9" ID)	0900 (0.9" ID)	Clear CL
1200 (1.2" ID)	1150 (1.0" ID)	Silver SL
1200 (1.2" ID)	1200 (1.2" ID)	Translucent Blue TB
1600 (1.6" ID)	1550 (1.5" ID)	
1600 (1.6" ID)	1600 (1.6" ID)	

POLYURETHANE COIL TUBE		
UC 08 50 - 5 BK		
POLYURETHANE COIL TUBE	TUBE DIA (O.D. & I.D.)	TUBE COLOR
METRIC TUBE	INCH TUBE	COLOR CODE
0054E (0.21" ID)	0050E (0.20" ID)	White WT
0640 (0.6" ID)	0600 (0.5" ID)	Black BK
0900 (0.9" ID)	0850 (0.75" ID)	Red RD
1200 (1.2" ID)	1150 (1.0" ID)	Blue BU
1200 (1.2" ID)	1200 (1.2" ID)	Yellow YL
1600 (1.6" ID)	1550 (1.5" ID)	Green GR
1600 (1.6" ID)	1600 (1.6" ID)	Clear CL
1600 (1.6" ID)	1600 (1.6" ID)	Silver SL
1600 (1.6" ID)	1600 (1.6" ID)	Translucent Blue TB

Uses

- Applicable for piping of various pneumatic devices.

Features

- Flexible at low temperatures.
- Light weight, excellent abrasion and chemical resistance, low price.
- More flexible than nylon tubes for easier piping work.
- Possible to select various colored tubes and use according to the work environment.

Specifications


Applicable fluid	compressed air (Not applicable to gases or liquids)
Operating pressure	0~150PSI / 0~9.8kgf/cm ² (0~990kPa)
Negative pressure	-29.5in Hg / -750mmHg(-750Torr)
Operating temperature range	32~140°F / 0~60°C

Structural drawing



Example of uses

- If the tube is forcibly pulled or folded after piping work is completed, it will adversely affect the product. Please refer to the radius of curvature below to proceed with the work.



PU Minimum bending radius at 23°C (mm)

Tube size	Ø3	Ø4	Ø6	Ø8	Ø10	Ø12	Ø14	Ø16
Bending radius	8	12	15	20	25	35	45	50

Tube size	Ø1/8	Ø5/32	Ø3/16	Ø1/4	Ø5/16	Ø3/8	Ø1/2
Bending radius	8	12	12	15	20	25	35

TUBE COLOR

COLOR	White	Black	Red	Blue	Yellow	Green	Clear	Silver	Translucent Blue
CODE	WT	BK	RD	BU	YL	GR	CL	SL	TB

CAUTIONS

- Make sure that the tube is pushed to the end of the fitting before using it. Otherwise, air may leak and the tube may fall out.
- When mounting the tube to the fitting, cut the tube at right angles and insert it inside. Make sure the tube does not fall out when gently pulled.
- Give some allowance when piping a tube, taking into account length change in the future.
- Where the tube may fall out to cause damage to people or property, be sure to fix in place.

WARNINGS

- Do not use for fluids other than air and water in the case of some products only. If needed for other fluids, please contact us beforehand.
- Check the tube for oval shape, damage to the outside diameter, or scratches. They may cause air leakage or tube falling out.
- Do not use for hot fluids such as water above 60°C. Heat and hydrolysis of tube materials may cause problems, including tube deformation.
- Do not apply in places where spatters occur. High fire risk caused by spatters.
- Tube may be destroyed by surge pressure when used in water.
- Do not apply in direct contact with liquids, such as cutting oil, lubricating oil, or coolant oil.
- Do not use in places where static electricity occurs or antistatic finishing is provided.
- Inappropriate for activated gases such as oxygen, hydrogen, and LPG. Do not use.

PU

Polyurethane tube



MODEL(Outer-Inner)

Tube Metric	Tube Inch
PU 0320	PU 1/8
PU 0420	PU 1/32
PU 0425	PU 1/16
PU 0640	PU 1/4
PU 0850	PU 1/8
PU 0855	PU 3/8
	PU 1/2

PE

Polyethylene tube



MODEL(Outer-Inner)

Tube Metric	Tube Inch
PE 0425	PE 1/32
PE 0640	PE 1/8
PE 0860	PE 1/4
PE 1070	PE 3/8
PE 1290	PE 1/2

PA

Polyamide tube



MODEL(Outer-Inner)

Tube Metric	Tube Inch
PA 0420	PA 1/32
PA 0425	PA 1/16
PA 0640	PA 1/4
PA 0860	PA 3/8
PA 1008	PA 1/2
PA 1209	PA 3/4

ETC

Tube Cutter



MODEL

ETC-20

SCPW



MODEL

SCPW 06
SCPW 08
SCPW 10
SCPW 12

UC

Coil tube




UC C



MODEL(Outer-Inner-Length)		
Tube Metric	Tube Metric	Tube Metric
w/o coupler		with coupler
UC 0640-3	UC 1065-10	UC 0850-5
UC 0640-5	UC 1280-5	UC 0850-7.5
UC 0640-7.5	UC 1280-7.5	UC 0850-10
UC 0640-10	UC 1280-10	UC 1065-5
UC 0850-5		UC 1065-7.5
UC 0850-7.5		UC 1065-10
UC 0850-10		UC 1280-5
UC 1065-5		UC 1280-7.5
UC 1065-7.5		UC 1280-10

Tube connecting method



Preparation

Prepare tube for application and a tube cutter and fitting connecting tool (spanner or wrench).

Cutting of tube

Cut the tube perpendicular to the axial direction using a tube cutter.

Connect with fitting

Using a spanner or wrench, tighten firmly within the recommended tightening torque range below.

Inserting of tube

Mark the tube insertion length on the tube and insert in a straight line relative to the fitting body. Now check whether the marking position is in the open sleeve section.

AIR GUNS



Product Code System

CA		01		F	
AIR GUN		NOZZLE SIZE(L)		COUPLING FORM	
		METRIC TYPE		CODE	TYPE
		Code	Length	Blank	PLUG
		00	0mm	F	Rc 1/4
		01	100mm		
		02	200mm	G	G 1/4
		03	300mm		

Uses

- Frequently used to clean mechanical facilities, products, and corners in workplaces.


Features

- Simple product design.
- Designed for user convenience, easy to adjust air injection.
- Nozzle of various lengths for wide use.
- Made of engineering plastic to be lightweight and shock resistant.

Specifications

Applicable fluid	compressed air (Not applicable to gases or liquids)
Operating pressure	0~150PSI / 0~9.8kgf/cm ² (0~990kPa)
Negative pressure	-29.5in Hg / -750mmHg(-750Torr)
Operating temperature range	32~140°F / 0~60°C

Structural drawing



CAUTIONS

- Be sure to note the safety precautions, the classification method of warning signs (p.25), and common precautions for fitting products (p.26) before using them.
- The product body is made of plastic. Be careful of excessive impact, rotation, and bending.
- Used for cleaning products and removing foreign substances and dust from machines. When cleaning various machines, stop operating the machine completely before using it.

WARNINGS

- When cleaning machines, stop operating the machine completely and use holding the body.
- Do not give strong impact to the body. Leakage may occur due to damage.

Product model name

CA



MODEL(L-T)

CA-50	CA-50G	CA-50F
CA-100	CA-100G	CA-100F
CA-200	CA-200G	CA-200F
CA-300	CA-300G	CA-300F

CAF



CB01




MODEL(L-T)

CB 01-100	CB 01-100G	CB 01-100F
CB 01-200	CB 01-200G	CB 01-200F
CB 01-300	CB 01-300G	CB 01-300F

CB01F



OIL EJECTOR LINES




Product Code System

OEL 01 R		
OIL EJECTOR LINE	THREAD (SIZE)	NOZZLE TYPE(L)
CODE	SIZE	CODE TYPE
01	R 1/4"	R Round
02	R 1/4"	F Flare
03	R 1/4"	
04	R 1/4"	
05	R 1/4"	

Product model name

OEL	
L	T
MODEL(T-L)	
OEL 01	
OEL 02	
OEL 03	
OEL 04	
OEL 05	

Structural drawing



Uses

- Mounted onto a machine tool, it directs the flow of cutting oil.

Features

- Effective in corrosion and chemical resistance. Non-conductive.
- Possible to change fluid flow to several directions.
- Made of plastic, semi-permanent, and light.
- Many types of products. Apply according to purpose.

CAUTIONS

- Be sure to note the safety precautions, the classification method of warning signs (p.25), and the common precautions for fitting products (p.24) before using them.
- The product body is made of plastic, so be careful of excessive impact, rotation, and bending when using.
- Use for supplying cutting oil and in the cleaning process during maintenance and inspection. Completely stop operation of the machine first.

1/4" SYSTEM		1/2" SYSTEM		3/4" SYSTEM
1/4" Hose	1/4" Y Fitting	1/2" Hose	1/2" Thread	3/4" Hose
1/8" Round Nozzle	1/8" Double Socket	1/4" Round Nozzle	1/2" Fitting	1/4" Round Nozzle
1/4" Round Nozzle	#11 Nozzle 1/8" Hole	3/8" Round Nozzle	1/2" 1/4" Y Reducer	3/8" Round Nozzle
1" Flare Nozzle	#13 Nozzle 1/8" Hole	1/4" Flare Nozzle	1/2" Double Socket	1" Flare Nozzle
R 1/8" Thread	1/4" Valve	1/2" Flare Nozzle	1/2" Valve	R 3/4" Thread
R 1/4" Thread	1/4" Thread Valve	R 3/8" Thread	#20 Nozzle 20 Hole	
			1/2" Thread valve	

COUPLERS / KOREA COUPLERS / SP COUPLERS / TSP COUPLERS / CAM-LOCK COUPLER



A company that dreams of a rich tomorrow,
Technology for the Future - CDC PNEUMATICS

COUPLERS



Product Code System

OSH 20									
H : KOREA COUPLER O : ONE TOUCH COUPLER B : BRASS COUPLER	COUPLING FORM		SCREW FORM		THREAD SIZE				
	CODE	TYPE	CODE	TYPE	SIZE	H	M	F	N
	S	Socket	H	Hose Stem	20	9	R $\frac{1}{4}$	Rc $\frac{1}{4}$	-
	P	Plug	M	Male Thread	30	11	R $\frac{1}{2}$	Rc $\frac{1}{2}$	-
			F	Female Thread	40	15	R $\frac{3}{4}$	Rc $\frac{3}{4}$	-
			N	Nut	400	15	R $\frac{1}{2}$	Rc $\frac{1}{2}$	-
					600	21	R $\frac{3}{4}$	Rc $\frac{3}{4}$	-
					800	27	R1	Rc1	-
					06	-	-	-	8x5
					10	-	-	-	10x6.5
					12	-	-	-	12x8

Uses

- Used to connect pipe for compressed air.
- May be used widely, e.g., for connecting the pneumatic tool hose and air piping in the factory.


Features

- One-way on-off coupler with an automatic on-off valve built into the hole.
- Of various materials and shapes, the coupler can be selected according to purpose and environment.
- Easy to use with plug and socket smoothly fastened and disconnected.


Specifications

Applicable fluid	compressed air (Not applicable to gases or liquids)
Material	Steel, brass
Operating pressure	0~150PSI / 0~9kgf/cm ² (0~980kPa).
Operating temperature range	32~140°F / 0~60°C

Structural drawing



Example of uses



CAUTIONS

- If air leaks due to wear or aging of the packing, replace the main body with a new one.
- Note that foreign substances and dust on the packing surface may cause water leakage.
- Wrongly selected packing material may cause leakage. After considering the suitability of rubber material for fluid type and temperature, select product to use.
- Be careful that fastening the coupler with excessive force may cause damage to the device or product.
- Do not apply where there is metal powder, sand, and dust. They may be a cause for defective coupler and equipment breakdown.

WARNINGS

- Avoid attaching or detaching the coupler under pressurized conditions. Please note that it may cause damage to the device and human life.
- Be aware that artificially applied curvature, tension, and impact may cause damage.
- Do not rotate the coupler in order to use as a replacement for the rotary or swivel joints.
- Avoid using a coupler when big vibration or impact applied by tools or devices could cause shock.
- May be difficult to fasten a coupler under residual pressure, so completely release the residual pressure before fastening.
- Do not arbitrarily disassemble the coupler.

Steel Coupler

SH



MODEL(T)
Hose Stem
SH 20
SH 30
SH 40
SH 400
SH 600
SH 800

SM



MODEL(T)
Thread R
SM 20
SM 30
SM 40
SM 400
SM 600
SM 800

SF



MODEL(T)
Thread Rc
SF 20
SF 30
SF 40
SF 400
SF 600
SF 800

SN



MODEL(T)
Hose Nut(ΦT)
SN 08
SN 10
SN 12

PH



MODEL(T)
Hose Stem
PH 20
PH 30
PH 40
PH 400
PH 600
PH 800

PM



MODEL(T)
Thread R
PM 20
PM 30
PM 40
PM 400
PM 600
PM 800

PF



MODEL(T)
Thread Rc
PF 20
PF 30
PF 40
PF 400
PF 600
PF 800

PN



MODEL(T)
Hose Nut(ΦT)
PN 08
PN 10
PN 12

Steel One - Touch Coupler

OSH



MODEL(T)
Hose Stem
OSH 20
OSH 30
OSH 40

OSM



MODEL(T)
Thread R
OSM 20
OSM 30
OSM 40

OSF



MODEL(T)
Thread Rc
OSF 20
OSF 30
OSF 40

OSN



MODEL(T)
Hose Nut(ΦT)
OSN 08
OSN 10
OSN 12

Coupler BSBM

BSH



MODEL(T)
Hose Stem
BSH 20
BSH 30
BSH 40

BSM



MODEL(T)
Thread R
BSM 20
BSM 30
BSM 40

BSF



MODEL(T)
Thread Rc
BSF 20
BSF 30
BSF 40

BPH



MODEL(T)
Hose Stem
BPH 20
BPH 30
BPH 40

BPM



MODEL(T)
Thread R
BPM 20
BPM 30
BPM 40

BPF



MODEL(T)
Thread Rc
BPF 20
BPF 30
BPF 40

Mold Coupler BSBM

KSH



MODEL(T)
Hose Stem
KSH 20
KSH 30A
KSH 30

KSM



MODEL(T)
Thread R
KSM 10
KSM 20
KSM 30

KSF



MODEL(T)
Thread Rc
KSF 10
KSF 20
KSF 30

KPH



MODEL(T)
Hose Stem
KPH 20
KPH 30A
KPH 30

KPM



MODEL(T)
Thread R
KPM 10
KPM 20
KPM 30

KPF



MODEL(T)
Thread Rc
KPF 10
KPF 20
KPF 30

Steel Line Coupler

LC2A



MODEL(T)
Thread/Rc 1/4"
LC 2A

LC3A



MODEL(T)
Thread/Rc 1/4"
LC 3A

LC03



MODEL(T)
Thread/Rc 1/4"
LC 03

OLC 2A



MODEL(T)
Thread/Rc 1/4"
OLC 2A

OLC 3A



MODEL(T)
Thread/Rc 1/4"
OLC 3A

Korea Coupler

HPH



MODEL(T)
Hose Stem
HPH 20
HPH 30
HPH 40

HPM



MODEL(T)
Thread R
HPM 20
HPM 30
HPM 40

HPF



MODEL(T)
Thread Rc
HPF 20
HPF 30
HPF 40

HPN



MODEL(T)
Hose Stem
HPN 08
HPN 10
HPN 12

HSH



MODEL(T)
Thread R
HSH 20
HSH 30
HSH 40

HSM



MODEL(T)
Thread Rc
HSM 20
HSM 30
HSM 40

HSF



MODEL(T)
Hose Stem
HSF 20
HSF 30
HSF 40

HSN



MODEL(T)
Thread R
HSN 08
HSN 10
HSN 12



SP COUPLERS



Product Code System

SP 01 S				
SP COUPLER	THREAD SIZE			COUPLING FORM
	SIZE	S	P	
	01	Rc 1/8	Rc 1/8	S Socket
	02	Rc 1/4	Rc 1/4	
	03	Rc 3/8	Rc 3/8	P Plug
	04	Rc 1/2	Rc 1/2	
	06	Rc 3/4	Rc 3/4	
	08	Rc 1	Rc 1	

Uses

- This coupler is to be applied to piping and equipment for steam, oil, chemicals, and air.


Features

- Widely used for vacuum applications. Easily handles fluids and vacuum resistant at 10mmHg when separated.
- On-off valves are built into both the socket and the plug. This medium-to-high pressure coupler is durable and hermetic compared to existing couplers.
- High safety, two-way on-off type coupler.

Specifications

Operating fluids	Air, Water, Gasoline, Oil, Steam
Material	Brass
Operating pressure	Rc 1/8~Rc 3/8 : 0~50kgf/cm ² (5000kPa) Rc 1/2~Rc 1 : 0~30kgf/cm ² (3000kPa)
Operating temperature range	-20 ~ 80℃

Structural drawing



Example of uses

- Compatibility** : Coupler of different sizes cannot be connected.
- Direction of attaching and fastening of coupler** :
Fluid flows through either plug or socket.
Minimum cross-sectional area (mm²)

Product name	01 SP	02 SP	03 SP	04 SP	06 SP	08 SP	Note
Minimum cross-sectional area	10	25	43	90	190	305	FKM/Intri



CAUTIONS

- Be sure to note the precautions and warnings of the coupler before use.
- The SP coupler may not be fastened due to manufacture to different specifications. Please contact us to select and use the product.

WARNINGS

- Avoid attaching or detaching the coupler under pressurized conditions. Please note that this may cause damage to the device and human life.
- Be aware that artificially applied curvature, tension, and impact may cause damage.
- Do not rotate the coupler in order to use as a replacement for the rotary or swivel joints.
- Avoid using a coupler when a big vibration or impact applied by tools or devices may cause shock.
- May be difficult to fasten a coupler under residual pressure, so completely release the residual pressure before fastening.
- Do not arbitrarily disassemble the coupler.

Product model name



MODEL(T)	
Thread	Rc
SP 01S	
SP 02S	
SP 03S	
SP 04S	
SP 06S	
SP 08S	
Thread Rc	
SUS-SP 01S	
SUS-SP 02S	
SUS-SP 03S	
SUS-SP 04S	
SUS-SP 06S	
SUS-SP 08S	

MODEL(T)	
Thread	Rc
SP 01P	
SP 02P	
SP 03P	
SP 04P	
SP 06P	
SP 08P	
Thread Rc	
SUS-SP 01P	
SUS-SP 02P	
SUS-SP 03P	
SUS-SP 04P	
SUS-SP 06P	
SUS-SP 08P	



TSP COUPLERS



Product Code System

TSP 01 TS		
TSP COUPLER	THREAD SIZE	COUPLING FORM
	SIZE TS TP	CODE TYPE
	01 Rc 1/8 Rc 1/8	S Socket
	02 Rc 1/4 Rc 1/4	P Plug
	03 Rc 1/2 Rc 1/2	
	04 Rc 3/4 Rc 3/4	
	06 Rc 1 Rc 1	
	08 Rc 1 1/2 Rc 1 1/2	

Uses

- This coupler is to be applied to piping and equipment for steam, oil, chemicals, and air.
- Widely used for vacuum applications. Easily handles fluids and is vacuum resistant at 10mmHg when separated.


Features

- On-off valves are built into both the socket and the plug. This medium-to-high pressure coupler is very durable and hermetic compared to existing couplers.
- High safety, two-way on-off type coupler.

Specifications

Operating fluids	Air, Water, Gasoline, Oil, Steam
Material	Brass
Operating pressure	Rc 1/8 to Rc 3/8: 0 to 50kgf/cm ² (5,000kPa) Rc 1/2 to Rc 1: 0 to 30kgf/cm ² (3,000kPa)
Operating temperature range	-20°C to 80°C

Structural drawing



Example of uses

- Compatibility:** Coupler of different sizes cannot be connected
- Direction of attaching and fastening of coupler:** Fluid flows through either plug or socket.

Minimum cross-sectional area (mm²)

Product name	01 3P	02 3P	03 3P	04 3P	06 3P	08 3P	Note
Minimum cross-sectional area	10	25	43	90	180	305	[10kV/mm]



CAUTIONS

- Be sure to note the precautions and warnings of the coupler product before use.
- The 3P coupler may not be fastened due to manufacture to different specifications. Please contact us to select and use the product.

WARNINGS

- Avoid attaching or detaching the coupler under pressurized conditions.
- Please note that this may cause damage to the device and human life.
- Be aware that artificially applied curvature, tension, and impact may cause damage.
- Do not rotate the coupler in order to use as a replacement for the rotary or swivel joints.
- Avoid using a coupler when a big vibration or impact applied by tools or devices may cause shock.
- May be difficult to fasten a coupler under residual pressure, so completely release the residual pressure before fastening.
- Do not arbitrarily disassemble the coupler.

Product model name

TS		TP		TM	
MODEL(T)	Thread Rc	MODEL(T)	Thread Rc	MODEL(T)	Thread Rc
TSP 01TS	SUS-TSP 01TS	TSP 01TP	SUS-TSP 01TP	TSP 01TM	SUS-TSP 01TM
TSP 02TS	SUS-TSP 02TS	TSP 02TP	SUS-TSP 02TP	TSP 02TM	SUS-TSP 02TM
TSP 03TS	SUS-TSP 03TS	TSP 03TP	SUS-TSP 03TP	TSP 03TM	SUS-TSP 03TM
TSP 04TS	SUS-TSP 04TS	TSP 04TP	SUS-TSP 04TP	TSP 04TM	SUS-TSP 04TM
TSP 06TS	SUS-TSP 06TS	TSP 06TP	SUS-TSP 06TP	TSP 06TM	SUS-TSP 06TM
TSP 08TS	SUS-TSP 08TS	TSP 08TP	SUS-TSP 08TP	TSP 08TM	SUS-TSP 08TM

TWO-TOUCH FITTINGS BSBM



Product Code System

METRIC - BSPT(R)

CC 6×4-01

TUBE DIA.			THREAD SIZE	
CODE	O.D.	I.D.	R/PT	THREAD
4×2	Φ4	Φ2	01	R1/8
4×2.5	Φ4	Φ2.5	02	R1/4
6×4	Φ6	Φ4	03	R1/2
8×5	Φ8	Φ5	04	R3/4
10×6	Φ10	Φ6		
10×8	Φ10	Φ8		
12×8	Φ12	Φ8		
12×9	Φ12	Φ9		
16×12	Φ16	Φ12		
16×13	Φ16	Φ13		

INCH - BSPT(R)

CC 1/4-01

TUBE DIA(Nylon Tube)			THREAD SIZE	
CODE	O.D.	I.D.	R/PT	THREAD
1/8	Φ3.18	Φ2.0	01	R1/8
3/16	Φ4.76	Φ3.0	02	R1/4
1/4	Φ6.35	Φ4.57	03	R1/2
5/16	Φ8.0	Φ5.0	04	R3/4
3/8	Φ9.53	Φ6.99		
1/2	Φ12.7	Φ9.56		

Uses

- Screw tightening type fitting with a high tube retaining force, which can be easily attached and detached in a compact piping space.
- Easy to use in shock- and vibration-prone equipment and piping environments.


Features

- Has insert attached for high pressure and vibration resistance.
- Two-touch fitting to connect and fix tube more securely.
- Screw threads are coated for efficient piping work.

Specifications

Applicable fluid	Air, Oil, Water
Operating pressure	0~150PSI / 0~9.9kgf/cm ² (0~990kPa)
Negative pressure	-750mmHg(-750 Torr)
Operating temperature range	Air: 40℃~+80℃
	Water: 0℃~+70℃
	Oil: 40℃~+80℃

Structural drawing



Example of uses



CAUTIONS

- Be sure to note the safety precautions, the classification method of warning signs (25p), and the common precautions for fitting products (P24) before using them.
- Assemble with reference to the proper fastening torque for fittings. (26p)
- The standard is to fasten by hand and rotate 3-5 turns using the tool. Assembling too hard may break the screw thread.
- If insertion section of the tube is dirty, wipe off the dirt from the surface before use.
- The sleeve of this product should not be reused. After using once, replace with a new one.

WARNINGS

- Do not use any products that have been processed secondarily or dismantled or modified.
- Avoid piping under tension or piping with sudden curvature change at the tube insertion section of the fitting.
- Do not use in environments with inflammable or corrosive gas.
- Do not allow hot fluid to be in contact with the tube and fittings. May cause burns to the human body.

CC



MODEL(ΦD-T)

Tube Metric - Thread R		Tube Inch - Thread R	
CC 4×2-01	CC 8×6-02	CC 12×8-04	CC 1/4-01
CC 4×2-02	CC 8×6-03	CC 12×9-02	CC 1/4-02
CC 4×2.5-01	CC 10×6.5-02	CC 12×9-03	CC 1/4-03
CC 6×4-01	CC 10×6.5-03	CC 12×9-04	CC 1/4-04
CC 8×4-02	CC 10×6.5-04	CC 16×12-03	CC 1/2-01
CC 8×4-03	CC 10×8-02	CC 16×12-04	CC 1/2-02
CC 8×5-01	CC 10×8-03	CC 16×13-03	CC 1/2-03
CC 8×5-02	CC 10×8-04	CC 16×13-04	CC 1/2-04
CC 8×5-03	CC 12×8-02		
CC 8×6-01	CC 12×8-03		

CC
INCH

CL



MODEL(ΦD-T)

Tube Metric - Thread R		Tube Inch - Thread R	
CL 4×2-01	CL 8×6-02	CL 12×8-04	CL 1/4-01
CL 4×2-02	CL 8×6-03	CL 12×9-02	CL 1/4-02
CL 4×2.5-01	CL 10×6.5-02	CL 12×9-03	CL 1/4-03
CL 6×4-01	CL 10×6.5-03	CL 12×9-04	CL 1/4-04
CL 6×4-02	CL 10×6.5-04	CL 16×12-03	CL 1/2-01
CL 8×4-02	CL 10×8-02	CL 16×12-04	CL 1/2-02
CL 8×5-01	CL 10×8-03	CL 16×13-03	CL 1/2-03
CL 8×5-02	CL 10×8-04	CL 16×13-04	CL 1/2-04
CL 8×5-03	CL 12×8-02		
CL 8×6-01	CL 12×8-03		

CL
INCH

CT



MODEL(ΦD-T)

Tube Metric - Thread R	
CT 4×2-01	CT 10×6.5-02
CT 4×2-02	CT 10×6.5-03
CT 4×2.5-01	CT 10×6.5-04
CT 6×4-01	CT 10×8-02
CT 6×4-02	CT 10×8-03
CT 6×4-03	CT 10×8-04
CT 8×5-01	CT 12×8-02
CT 8×5-02	CT 12×8-03
CT 8×5-03	CT 12×8-04
CT 8×6-01	CT 12×9-02
CT 8×6-02	CT 12×9-03
CT 8×6-03	CT 12×9-04

CUC

CUC
INCH

MODEL(ΦD)

Tube Metric	Tube Inch
CUC 4×2	CUC 1/4
CUC 4×2.5	CUC 1/8
CUC 6×4	CUC 1/2
CUC 8×5	
CUC 8×6	
CUC 10×6.5	
CUC 10×8	
CUC 12×8	
CUC 12×9	

CUL



MODEL(ΦD)

Tube Metric	Tube Inch
CUL 4×2	
CUL 4×2.5	
CUL 6×4	
CUL 8×5	
CUL 8×6	
CUL 10×6.5	
CUL 10×8	
CUL 12×8	
CUL 12×9	

CUT



MODEL(ΦD)

Tube Metric	Tube Inch
CUT 4×2	CUT 1/4
CUT 4×2.5	CUT 1/8
CUT 6×4	CUT 1/2
CUT 8×5	
CUT 8×6	
CUT 10×6.5	
CUT 10×8	
CUT 12×8	
CUT 12×9	

CUT
INCH

CSM



MODEL(ΦD)

Tube Metric	Tube Inch
CSM 4	
CSM 6	
CSM 8	
CSM 10	
CSM 12	
CSM 16	

CSN



MODEL(ΦD)

Tube Metric	Tube Inch
CSN 4	CSN 1/8
CSN 6	CSN 1/4
CSN 8	CSN 1/2
CSN 10	CSN 3/8
CSN 12	CSN 1/2
CSN 16	CSN 1/2

CSN
INCH

NUT

NUT
INCH

MODEL(ΦD)

Tube Metric	Tube Inch
NUT 4	NUT 1/16
NUT 6	NUT 1/4
NUT 8	NUT 1/8
NUT 10	NUT 1/2
NUT 12	
NUT 16	

BARB FITTINGS



Product Code System

BCC 04-M5

BARB FITTINGS

류브 직경

CODE	SIZE
03	Ø3×Ø2
04	Ø4×Ø2.5
06	Ø6×Ø4

나사 규격

CODE	SIZE
M5	M5×0.8
01	R 1/4
02	R 1/2

Uses

- This product is used together with tubes in equipment that has been vacuum generated.

Features

- Compact product that can be used when piping in small spaces.
- Two-touch type can be installed without tools.
- Tubes made of PA and PU are available.
- The body is treated with electroless nickel plating.


Specifications

Operating fluid	Air
Operating pressure	10Bar
Vacuum pressure	-100kPa
Operating temperature range	-5 ~ 60℃

Structural drawing



Example of uses



CAUTIONS

- Do not arbitrarily modify product.
- Barb fitting product line should not be used for water.

BCC



MODEL(T)

Thread **M**

BCC 04-M5

BCC 06-M5

BCC 04-1

BCC 06-1

BCLL



MODEL(T)

Thread **M**

BCLL 04-M5

BCLL 04-M5

BCL



MODEL(T)

Thread **M**

BCL 04-M5

BCL 06-M5

BP



MODEL(T)

Thread **M/R**

BP M5

BP 01

BP 02

BHC



MODEL(T)

Thread **M**

BHC 04-M5

BHC 06-M5

BHLL



MODEL(T)

Thread **M**

BHLL 03-M5

BHLL 04-M5

BHLL 06-M5

BHL



MODEL(T)

Thread **M**

BHL 03-M5

BHL 04-M5

BHL 06-M5



- Although the compatibility is proved as Excellent or Good, it may not be suitable in some purposes of applications.
- Be sure to refer to actual using condition.

Chemical name Density(%, Temperature(℃))	Fitting				Tube Type				Seal material			
	BRASS	SUS304	SUS316	PP	Urethane	Nylon	Polyethylene	Fluorine	NER	EPDM	FKM	FKM
Caustic soda (10% 20℃)	△	△	△	○	△	○	○	○	○	○	○	○
Caustic soda (30% 20℃)	△	△	△	○	△	○	○	○	○	○	○	○
Caustic soda (30% 70℃)	△	△	△	○	△	○	○	○	○	○	○	○
Gasoline	○	○	○	○	△	○	○	△	○	○	○	○
Air	○	○	○	○	○	○	○	○	○	○	○	○
Sodium perborate	×	—	○	○	○	—	○	○	○	○	○	○
Sodium peroxide	×	—	○	—	—	—	×	○	○	○	○	○
Hydrogen peroxide (5%, 20℃)	×	○	○	○	○	○	○	○	○	○	○	○
Hydrogen peroxide (5%, 20℃)	×	○	○	○	○	△	△	○	○	○	○	○
Hydrogen peroxide (30%, 20℃)	×	○	○	○	○	×	×	○	○	○	○	○
Perchloric acid	×	×	×	×	○	×	×	○	○	○	○	○
Grease	○	○	○	○	△	○	△	○	○	○	○	○
Sodium silicate	△	—	○	○	○	○	○	○	○	○	○	○
Glycerin 글리세린	○	○	○	○	○	○	○	○	○	○	○	○
Naphtha	△	○	○	○	△	△	○	△	○	△	×	○
Naphthalene	△	—	△	○	○	△	○	△	○	×	×	○
Nitropropane	△	—	—	○	—	—	○	○	○	○	○	○
Kerosene	○	○	○	○	△	○	○	○	○	○	○	○
Dichloro benzene	△	—	—	△	△	×	×	○	—	—	—	—
Linoleic acid	△	—	—	○	—	△	△	○	○	×	○	○
Maleic acid	△	△	△	—	—	△	○	○	○	△	○	○
Cottonseed oil	△	○	○	○	—	○	○	○	○	○	○	○
Methane	○	—	△	○	○	○	○	○	○	○	○	○
Methyl alcohol(Methanol)	○	△	○	○	○	○	○	○	○	○	○	△
Methyl ethyl ketone(MEK)	○	△	○	○	○	×	○	○	○	×	×	×
Methyl isobutyl ketone(MIBK)	△	—	△	○	○	○	×	○	○	×	△	×
Monothanolamine	—	—	△	○	—	○	△	○	×	○	×	×
Monochlorobenzene	—	—	—	○	—	×	×	×	○	×	×	○
Chloroacetic acid	—	—	—	△	△	×	×	×	○	—	—	—
Hydrofluoric acid Anhydride	×	—	×	×	—	×	×	×	○	—	○	—
Acetic Anhydride	×	○	○	×	—	△	×	△	○	△	○	×
Water (24℃)	○	○	○	○	○	○	○	○	○	○	○	○
Water (100℃)	×	○	○	△	×	△	△	△	○	—	—	—
Sea Water	△	○	○	○	○	○	○	○	○	○	○	○
Bunker oil	△	—	○	—	—	—	○	○	○	○	○	○
Benzene(Benzol)	×	△	△	○	○	△	×	○	×	×	×	○
Butane	○	○	○	○	○	—	○	△	○	○	×	○
Fluorine	×	×	△	×	—	×	×	—	×	×	△	○
Borax	×	—	○	—	—	○	○	○	○	○	○	○
Boric acid	○	○	○	○	○	○	○	○	○	○	○	○
Amyl borate	—	—	—	○	—	△	—	△	○	×	○	○
Bromine	×	—	×	×	×	×	×	×	○	—	—	○
Arsenic acid	△	○	○	—	—	○	△	○	○	—	—	—
Carbon tetrachloride	△	△	△	○	○	×	△	×	○	△	×	○
Oxygen	○	○	○	○	○	○	○	○	○	○	○	○
Petroleum	—	—	—	○	○	×	○	○	○	×	○	○

Judgement Standard

◎ : Excellent ○ : Good △ : Require confirmation × : Incompatible - : No data

Chemical name Density(%, Temperature(℃))	Fitting				Tube Type				Seal material			
	BRASS	SUS304	SUS316	PP	Urethane	Nylon	Polyethylene	Fluorine	NER	EPDM	FKM	FKM
Salt Water	×	△	△	○	○	○	○	○	○	○	○	○
Soda water	—	—	—	○	○	○	○	○	○	○	○	○
Soda ash—Sodium carbonate	○	△	△	○	○	○	○	○	○	○	○	○
Pine oil	△	○	○	—	○	○	—	×	○	○	○	×
Oxalic acid	△	△	△	×	○	○	△	○	○	○	○	○
Ethyl oxalate	—	—	—	○	○	×	×	×	○	×	○	○
Magnesium hydroxide	△	△	△	×	○	△	○	○	○	○	○	○
Barium hydroxide	×	—	○	○	△	○	—	○	○	○	○	○
Ammonium hydroxide	×	△	○	○	×	○	△	○	○	×	○	○
Potassium hydroxide	△	△	△	×	○	△	△	○	○	○	○	○
Calcium hydroxide	△	△	△	×	○	△	○	○	○	○	○	○
Hydrogen	△	○	○	○	○	○	○	○	○	○	○	○
Mercury	×	—	△	—	○	—	○	○	○	○	○	○
Steam (150℃ or less)	○	—	○	△	△	×	×	×	○	×	○	×
Steam (150℃ or higher)	○	—	—	×	×	×	×	×	○	×	○	×
Vegetable oil	—	—	—	○	○	—	○	○	○	○	○	○
Salt water	△	△	△	○	○	○	○	○	○	○	○	○
Silicone greases	—	—	—	○	○	△	—	○	△	○	○	○
Silicone oil	—	—	—	○	○	△	—	○	△	○	○	○
Glue	△	—	△	—	—	○	○	○	○	—	—	—
Aniline oil	×	△	△	○	○	△	×	×	×	○	×	△
Amyl naphthalene	—	—	—	○	○	△	—	△	○	×	×	○
Amyl alcohol	○	△	△	○	○	○	○	○	○	○	○	○
Acetone	○	△	○	○	○	△	×	○	△	○	×	×
Acetamide	—	—	—	○	○	△	—	△	○	○	○	○
Acetaldehyde	○	○	○	○	○	○	○	○	○	×	○	×
Acetylene	×	○	○	○	○	○	○	○	○	○	○	○
Sulfurous acid	×	△	△	×	○	○	×	×	○	○	○	○
Sulfurous acid gas	—	—	○	△	○	○	×	×	△	○	○	○
Sodium sulfite	○	○	○	○	○	○	—	△	○	○	—	—
Ammonia (No water)	△	○	○	○	△	—	○	○	○	○	×	×
Ammonia gas (Cold)	×	○	○	○	△	×	△	△	○	○	○	×
Ammonia gas (Heat)	×	○	○	○	×	×	×	×	○	○	○	×
Liquid Ammonia	○	○	○	○	△	—	○	○	○	—	—	—
Chlorine Liquide	—	—	—	×	○	×	×	×	○	—	—	—
Liquidified petroleum gas(LPG)	○	○	○	○	○	△	—	○	△	○	×	○
Ethanolamine	—	—	—	○	△	△	—	△	△	○	○	×
Ethylene glycol	△	△	△	○	○	○	○	○	○	○	○	○
Ethyl cellulose	—	—	△	○	○	○	—	○	○	—	○	×
Ethyl alcohol(Ethanol)	○	○	○	○	○	○	△	○	○	○	○	○
Lye solution	—	—	—	○	○	○	—	○	○	○	○	○
Hydrochloric acid (10%, 20℃)	×	×	×	×	○	○	△	○	○	○	—	—
Hydrochloric acid (20%, 20℃)	×	×	×	×	△	○	×	×	○	○	—	—
Hydrochloric acid (20%, 80℃)	×	×	×	×	×	×	×	×	×	×	×	△
Hydrochloric acid (38%, 20℃)	×	×	×	×	×	×	×	×	×	×	○	○
Magnesium chloride	△	△	○	○	○	○	○	○	○	○	○	○

- Although the compatibility is proved as Excellent or Good, it may not be suitable in some purposes of applications.
- Be sure to refer in actual using condition.

Chemical name Density(g/ml, Temperature(°C))	Fitting						Tube Type				Seal material		
	BRASS	SUS304	SUS316	POM	PBT	PP	Urethane	Nylon	Polyester	Fluorine	NER	EPDM	FKM
Methylene chloride	○	○	○	○	—	×	×	×	×	○	×	×	○
Barium chloride	×	—	○	—	○	○	○	○	○	○	○	○	○
Zinc chloride	×	△	○	×	○	○	○	○	○	○	○	○	○
Acetyl chloride	—	—	△	×	—	×	×	×	×	—	—	—	○
Aluminium chloride	×	×	×	—	○	○	—	△	○	○	○	○	○
Ammonium chloride	×	△	△	○	○	○	○	○	○	○	○	○	○
Ethyl chloride	○	○	○	○	—	×	×	×	×	—	○	○	○
Sulfur chloride	×	—	△	—	—	△	—	△	○	△	×	○	○
Potassium chloride	△	△	△	○	○	○	○	○	○	○	○	○	○
Calcium chloride	○	△	△	○	○	○	○	○	○	○	○	○	○
Ozone	○	○	○	△	○	○	△	△	○	△	○	○	○
Oleic acid	△	△	△	△	○	△	○	△	○	△	○	○	○
Olive oil	△	○	○	○	○	○	○	○	○	○	○	○	○
Uric acid	—	—	—	○	○	—	×	○	—	○	—	—	—
Aqua acid	—	—	—	×	—	△	×	×	×	○	—	△	○
Lactic acid	×	△	△	○	○	○	×	○	○	○	○	○	○
Sulfur	×	○	○	○	—	○	△	○	○	○	×	○	○
Lubricating oil(Petroleum base)	○	○	○	○	○	×	○	○	×	○	○	×	○
Lubricating oil(Ester base)	○	○	○	○	○	×	×	×	×	○	—	—	—
Isocetane	○	○	○	○	○	×	△	○	×	○	×	○	○
Isopropyl alcohol	○	○	○	○	○	—	△	△	○	○	○	×	○
Isopropyl ether	○	○	○	○	○	—	△	△	○	○	○	×	○
Carbon disulfide	○	○	○	○	—	×	×	×	×	○	△	×	○
Phenyle disulfide	—	—	—	—	—	△	○	—	—	○	—	—	—
Carbon monoxide	○	○	○	○	○	○	○	○	○	○	○	○	○
Gelatin	○	○	○	○	○	○	○	○	○	○	○	○	○
Heavy water	—	—	—	○	○	○	○	○	○	○	—	—	—
Soap solutions	○	○	○	○	○	○	○	○	△	○	○	○	○
Sodium nitrate	○	○	○	○	○	○	○	○	○	○	○	○	○
Aluminium nitric	—	—	△	○	○	○	△	○	○	○	○	○	—
Ammonium nitric	×	○	○	○	○	○	○	○	○	○	○	○	○
Potassium nitric	△	△	△	○	○	○	○	○	○	○	○	○	○
Calcium nitric	—	—	—	○	○	○	—	○	○	○	○	○	○
Nitrogen	○	○	○	○	○	○	○	○	○	○	○	○	○
Natural gas	○	○	○	○	○	○	—	○	○	○	○	×	○
Acetic acid (10%, 20°C)	×	○	○	△	○	○	×	△	△	○	○	○	○
Acetic acid (50%, 20°C)	×	○	○	×	○	×	×	×	×	○	—	—	—
Acetic acid (50%, 70°C)	×	○	○	×	△	×	×	×	×	○	—	—	—
Acetic acid (100%, 20°C)	×	△	△	×	△	×	×	×	×	○	—	—	—
Lead acetate	—	△	—	—	○	○	—	○	○	○	○	○	○
Nickel acetate	—	—	△	—	○	○	—	○	○	○	○	○	×
Zinc acetate	—	—	—	○	○	○	—	○	○	○	○	○	×
Aluminium acetate	—	—	—	○	○	○	—	○	○	○	○	○	—
Calcium acetate	△	—	△	○	○	○	○	○	○	○	○	○	×
Cresol	○	△	△	△	○	○	×	×	△	△	×	×	○
Chlorosulfonic acid	△	×	×	×	○	×	—	×	×	○	×	×	△

Judgement Standard

○ : Excellent ○ : Good △ : Require confirmation × : Incompatible - : No data

Chemical name Density(g/ml, Temperature(°C))	Fitting						Tube Type				Seal material		
	BRASS	SUS304	SUS316	POM	PBT	PP	Urethane	Nylon	Polyacrlin	Fluorine	NER	EPDM	FKM
Chloroacetone	—	—	—	—	○	×	—	×	×	×	×	×	×
Chlorotoluene	—	—	—	○	○	×	—	×	×	○	×	×	×
Chloroform	○	○	○	△	△	×	○	×	×	○	×	×	×
Soybean oil	△	○	○	○	○	○	—	○	○	○	×	△	○
Tannic acid	×	△	△	○	—	○	△	○	○	○	○	○	○
Tar	△	△	○	—	—	○	○	○	○	○	○	×	○
Carbonic acid	○	△	△	—	—	○	△	○	○	○	○	—	—
Carbon dioxide	○	○	○	○	○	○	○	○	○	○	—	—	—
Sodium carbonate	○	△	△	○	○	○	○	○	○	○	—	—	—
Ammonium carbonate	—	△	△	○	○	○	—	○	○	○	×	○	—
Toluene	○	○	○	○	△	△	△	○	△	○	×	×	○
Triacetin	—	—	—	—	—	○	—	—	○	—	○	○	×
Phenol	○	○	○	×	○	○	×	×	○	○	—	○	○
Glucose	○	○	○	○	○	○	○	○	○	○	○	○	○
Freon11	○	○	○	○	○	—	—	○	—	○	○	×	○
Freon12	○	○	○	○	○	—	—	○	—	○	○	○	○
Freon21	○	○	○	○	○	—	—	○	—	○	×	×	×
Freon22	○	○	○	○	○	—	—	○	—	○	×	○	×
Freon113	○	○	○	○	○	—	—	○	—	○	○	×	○
Freon114	○	○	○	○	○	—	—	○	—	○	○	○	○
Propane	○	○	○	○	○	○	○	○	○	○	○	×	○
Propylene	○	○	○	○	○	—	○	○	—	○	×	×	○
Castor oil	○	○	○	○	○	○	△	△	○	○	○	○	○
Hexane	○	○	○	○	○	△	△	○	×	○	○	×	○
Sulfuric acid (10%, 20℃)	×	×	×	×	○	○	×	○	○	○	×	○	○
Sulfuric acid (10%, 70℃)	×	×	×	×	×	△	×	×	△	○	—	—	—
Sulfuric acid (30%, 20℃)	×	×	×	×	△	○	×	×	○	○	—	—	—
Sulfuric acid (30%, 70℃)	×	×	×	×	×	△	×	×	△	○	—	—	—
Sulfuric acid (98%, 20℃)	×	×	×	×	×	×	×	×	×	○	—	—	—
Sulfuric acid (smoke, 70℃)	×	×	×	×	×	×	×	×	×	○	—	—	—
Sodium sulfate	○	△	△	○	○	○	○	○	○	○	○	○	○
Nickel sulfate	—	△	○	—	○	○	—	○	○	○	○	○	○
Copper sulfate	○	△	○	○	○	○	○	○	○	○	○	○	○
Magnesium sulfate	○	○	○	—	○	○	○	○	○	○	○	○	○
Methyl sulfate	—	—	—	—	○	×	×	×	△	○	—	—	—
Barium sulfate	△	○	○	—	○	○	—	○	○	○	○	○	○
Aluminium sulfate	×	○	○	○	○	○	—	○	○	○	○	○	○
Ammonium sulfate	△	△	△	△	○	○	○	○	○	○	○	○	—
Lead sulfate	△	△	△	△	—	○	○	○	○	○	○	—	—
Sodium sulfide	×	△	△	△	○	○	○	○	○	○	○	○	○
Barium sulfide	—	△	○	○	○	○	—	○	○	○	○	○	○
Zinc sulfide	△	○	○	○	○	○	△	×	○	○	○	—	—
Calcium sulfide	—	—	△	○	○	○	—	○	○	○	○	○	○
				</									

